

ELAND[®]
CABLES

Veriflex[®] DeviceNet Thick LSZH Cable



Eland Product Group: VBU

APPLICATION

Veriflex[®] DeviceNet Thick cable for fixed and occasional flexing indoor applications in CAN technologies. Connects industrial devices, motor starters and PLCs. Commonly used as trunk cables for industrial ethernet installations.

CHARACTERISTICS

Maximum Operating Voltage
300V

Temperature Rating
-30°C to +80°C

Minimum Bending Radius
15 x overall diameter

CONSTRUCTION

Conductor

Data Pair: Stranded tinned copper wires
Power Supply Pair: Stranded tinned copper wires

Insulation

Data Pair: Foam-Skin Polyethylene
Power Supply Pair: Solid Polyethylene

Individual Pair Shield

AL/PET (Aluminium/Polyester Tape)

Drain Wire

Tinner Copper

Overall Shield

TCWB (Tinned Copper Wire Braid)

Separation

PET (Polyester Tape)

Sheath

LSZH (Low Smoke Zero Halogen)

Core Identification

Data Pair: ○ White ● Blue
Power Supply Pair: ● Black ● Red

Sheath Colour

● Violet

BSI KITEMARK™ TESTED



Cables are tested and verified by The Cable Lab[®] to confirm they meet the quality standards required of the BSI Cable TESTED Verification Kitemark™.

STANDARDS

BS EN/IEC 61034-1/2, IEC 60754-1

Flame Retardant according to BS EN/IEC 60332-1-2



ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab[®], an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab[®] as meeting the requirements of the BSI RoHS Trusted Kitemark™.



DIMENSIONS

ELAND PART NO.	NOMINAL CROSS SECTIONAL AREA mm ²		CONDUCTOR AWG		NOMINAL DIAMETER OF OUTER SHEATH mm	NOMINAL WEIGHT kg/km
	Data Pair	Power Supply Pair	Data Pair	Power Supply Pair		
VBUDNT04G7LSV10	0.93	1.93	18/19	15/19	11.9	220

ELECTRICAL CHARACTERISTICS AT 20°C

DC CONDUCTOR RESISTANCE Ω/km		CAPACITANCE AT 800 HZ DATA PAIR nF/km	IMPEDANCE ≥ 1 MHz DATA PAIR Ω	ATTENUATION DATA PAIR dB/100m			DIELECTRIC STRENGTH kVac / 1 min	MINIMUM INSULATION RESISTANCE GΩ×km	TRANSFER IMPEDANCE AT 10 MHz mΩ/m
Data	Power Supply Pair			AT 125 kHz	AT 500 kHz	AT 1 MHz			
23.2	11.3	40	120	0.4	0.8	1.25	2.0	5.0	15

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.