

ELAND[®]
CABLES

6181Y / BS 6004 Cable



Eland Product Group: A1Y

APPLICATION

Fixed installation in dry or damp areas for domestic and light industrial wiring. Also used in connection to (smart)meters.

CHARACTERISTICS

Voltage Rating Uo/U
300/500V

Temperature Rating
Fixed: -15°C to +70°C

Minimum Bending Radius
Up to 6mm² - Fixed: 3 x overall diameter
10mm² to 25mm² - Fixed: 4 x overall diameter

CONSTRUCTION

Conductor
1mm² to 2.5mm²: Class 1 solid copper conductor
4mm² to 25mm²: Class 2 stranded copper conductor

Insulation
PVC (Polyvinyl Chloride)

Sheath
PVC (Polyvinyl Chloride)

Insulation Colour
● Blue ● Brown

Sheath Colour
● Grey

CABLE THIRD-PARTY ACCREDITATION



Cables are tested and accredited by BASEC, The British Approvals Service for Cables

STANDARDS

BS 6004, BS EN 60228

Flame Retardant according to BS EN / IEC 60332-1-2



ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



DIMENSIONS

ELAND PART NO.	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER OF CONDUCTOR mm	NOMINAL THICKNESS OF INSULATION mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A1YGR/*0010	1	1.13	0.6	4.1	28
A1YGR/*0015	1.5	1.38	0.7	4.6	34
A1YGR/*0025	2.5	1.76	0.8	5.3	49
A1YGR/*0040	4	2.5	0.8	6.1	75
A1YGR/*0060	6	3	0.8	6.7	99
A1YGR/*010	10	3.85	1	8.1	155
A1YGR/*016	16	4.8	1	9.3	225
A1YGR/*025	25	5.9	1.2	11.1	340

*Designates the sheath colour. For each Eland Cables part number replace with the colour code as listed below e.g. A1YGR/BL0010 = 1mm² Blue

COLOUR CODES

COLOUR	Blue	Brown
CODE	BL	BR

CONDUCTORS

Class 1 Solid Conductors for Single Core and Multi-Core Cables

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	
	Circular, Annealed Copper Conductors	
	Plain Wires	Metal-Coated Wires
1	18.1	18.2
1.5	12.1	12.2
2.5	7.41	7.56

The above table is in accordance with BS EN 60228 (previously BS 6360)

Class 2 Stranded Conductors for Single Core and Multi-Core Cables

NOMINAL CROSS SECTIONAL AREA mm ²	MINIMUM NO. OF WIRES IN CONDUCTOR mm						MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	
	Circular		Circular Compacted		Shaped		Annealed Copper Conductor	
	Cu	Al	Cu	Al	Cu	Al	Plain Wires	Metal-Coated Wires
4	7	-	6	-	-	-	4.61	4.7
6	7	-	6	-	-	-	3.08	3.11
10	7	7	6	6	-	-	1.83	1.84
16	7	7	6	6	-	-	1.15	1.16
25	7	7	6	6	6	6	0.727	0.734

The above table is in accordance with BS EN 60228 (previously BS 6360)

ELECTRICAL CHARACTERISTICS

Current Carrying Capacity

NOMINAL CROSS SECTIONAL AREA mm ²	REFERENCE METHOD A (ENCLOSED IN CONDUIT IN THERMALLY INSULATING WALL ETC) Amps		REFERENCE METHOD A (ENCLOSED IN CONDUIT IN THERMALLY INSULATING WALL ETC) Amps		REFERENCE METHOD C (CLIPPED DIRECT) Amps		REFERENCE METHOD F (IN FREE AIR OR ON A PERFORATED CABLE TRAY ETC) HORIZONTAL OR VERTICAL ETC) Amps				
	2 Cables Single-Phase AC or DC	3 or 4 Cables Three-Phase AC	2 Cables Single-Phase AC or DC	3 or 4 Cables Three-Phase AC	2 Cables Single-Phase AC or DC	3 or 4 Cables Three-Phase AC	Touching			Spaced by one diameter	
							2 Cables Single-Phase AC or DC flat	3 Cables Three-Phase AC flat	3 Cables Three-Phase AC trefoil	Horizontal	Vertical
1	11	10.5	13.5	12	15.5	14	-	-	-	-	-
1.5	14.5	13.5	17.5	15.5	20	18	-	-	-	-	-
2.5	20	18	24	21	27	25	-	-	-	-	-
4	26	24	32	28	37	33	-	-	-	-	-
6	34	31	41	36	47	43	-	-	-	-	-
10	46	42	57	50	65	59	-	-	-	-	-
16	61	56	76	68	87	79	-	-	-	-	-
25	80	73	101	89	114	104	131	114	110	146	130

Ambient temperature: 30°C

Conductor operating temperature: 70°C

The above table is in accordance with Table 4D1A of the 17th Edition of IEE Wiring Regulations.

VOLTAGE DROP

NOMINAL CROSS SECTIONAL AREA mm ²	2 CABLES DC mV/A/m	2 CABLES SINGLE-PHASE AC mV/A/m						3 OR 4 CABLES THREE-PHASE AC mV/A/m														
		Reference Methods A and B enclosed in conduit or trunking)			Reference Methods C, F and G (clipped direct, on tray or in free air)			Reference Methods A and B enclosed in conduit or trunking)			Reference Methods C, F and G (clipped direct, on tray or in free air)											
					Cables Touching		Cables Spaced*					Cables touching, Trefoil			Cables touching, Flat			Cables spaced*, Flat				
1	44	44			44		44		38			38			38			38				
1.5	29	29			29		29		25			25			25			25				
2.5	18	18			18		18		15			15			15			15				
4	11	11			11		11		9.5			9.5			9.5			9.5				
6	7.3	7.3			7.3		7.3		6.4			6.4			6.4			6.4				
10	4.4	4.4			4.4		4.4		3.8			3.8			3.8			3.8				
16	2.8	2.8			2.8		2.8		2.4			2.4			2.4			2.4				
25	1.75	r	x	z	r	x	z	r	x	z	r	x	z	r	x	z	r	x	z	r	x	z
		1.80	0.33	1.80	1.75	0.20	1.75	1.75	0.29	1.80	1.50	0.29	1.55	1.50	0.175	1.50	0.15	0.25	1.55	1.50	0.32	1.55

Conductor operating temperature: 70°C

r = Resistive Component

x = Reactive Component

z = Impedance Value

* Spacings larger than one cable diameter will result in larger volt drop.

DE-RATING FACTORS

For Ambient Air Temperatures other than 30°C

AMBIENT TEMPERATURE	25°C	30°C	35°C	40°C	45°C	50°C	55°C	60°C
DE-RATING FACTOR	1.03	1.00	0.94	0.87	0.79	0.71	0.61	0.50

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.