

Copper Split Concentric BS 7870 PVC Cable



Eland Product Group: A1S

APPLICATION

Used by distribution network operators (DNO's) when providing the final connection to domestic properties. Also suitable for sub main distribution and particularly used within high-rise buildings and street lighting systems.

CHARACTERISTICS

Voltage Rating Uo/U
0.6/1KV

Temperature Rating
-15°C to +70°C

Minimum Bending Radius
8 x overall diameter

CONSTRUCTION

Conductor
Class 2 stranded copper conductor

Insulation
XLPE (Cross-Linked Polyethylene)

Neutral Conductor
Plain copper wires covered by a blue polymeric compound

Earth Continuity Conductor
Plain copper wires

String Separator
Non-hydroscopic separator

Sheath
PVC (Polyvinyl Chloride)

Sheath Colour
● Black

STANDARDS

BS EN 60228, BS 7870-3-21

Flame Retardant according to BS EN/IEC 60332-1-2



ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A1S/321C/1040	1	4	10	190
A1S/321C/116	1	16	14	530
A1S/321C/125	1	25	16	710
A1S/321C/335	3	35	28.5	1900

CONDUCTORS

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM DIAMETER OF WIRES IN CONDUCTOR mm	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	
		Plain Wires	Metal-Coated Wires
4	4.61	4.8	4.8
16	1.15	1.2	1.2
25	0.727	0.76	1.2
35	0.524	0.55	0.76

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		
	In Air	Clipped Direct	Enclosed in Conduit on a Wall
4	42	41	37
16	100	99	88
25	135	130	117
35	129	120	110

Conductor Operating Temperature: 90°C

Ambient Temperature: 30°C

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.