



# 2kV 6mm<sup>2</sup> XLPE PVC Cable



Eland Product Group: AGL

## APPLICATION

A single core 2kV unscreened, PVC sheathed power cable. Used for the interconnection of Airfield Lighting systems. Suitable for installation in conduit, duct aerial and direct burial.

## CHARACTERISTICS

### Voltage Rating

2kV

### Temperature Rating

-25°C to +90°C

### Minimum Bending Radius

9 x overall diameter

## CONSTRUCTION

### Conductor

Class 2 stranded copper conductor

### Insulation

XLPE (Cross-Linked Polyethylene)

### Sheath

PVC (Polyvinyl Chloride)

### Sheath Colour

● Black

## STANDARDS

FAA L-824C, IEC/EN 60228

## THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



## REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.



## DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	RADIAL THICKNESS OF INSULATION mm	NOMINAL OVERALL DIAMETER mm	MAXIMUM RESISTANCE OF CONDUCTOR ohms/km
AGL2KV006PV	1	6	1.35	8.05	3.08

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.