

ELAND[®]
CABLES

N2XS(F)2Y - 12/20 (24)kV Cable



Eland Product Group: A9X

APPLICATION

Medium voltage cables for distribution networks; also for connection to generation units and plant and process connection. For installation in ground, in water outdoors, indoors and in cable ducts for power stations, industry, and distribution networks.

CHARACTERISTICS

Voltage Rating U_0/U (Um)
12/20 (24)kV

Temperature Rating
-20°C to +90°C

Minimum Bending Radius
15 x overall diameter

CONSTRUCTION

Conductor
Class 2 stranded copper conductor

Inner Semi-Conductive Layer
Semi-conductive material

Insulation
XLPE (Cross-Linked Polyethylene)

Outer Semi-Conductive Layer
Semi-conductive material

Screen
Copper wires and copper tape

Tape
Water-swellable tape

Outer Sheath
PE (Polyethylene)

Sheath Colour
● Black

STANDARDS

DIN VDE 0276-620, HD 620, BS EN/IEC 60228,
IEC 60502-2



ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²		NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
		Conductor	Copper Wire Screen		
A9XF20KV1035	1	35	16	32	1000
A9XF20KV1050	1	50	16	33	1150
A9XF20KV1070	1	70	16	35	1350
A9XF20KV1095	1	95	16	36	1600
A9XF20KV1120	1	120	16	38	1850
A9XF20KV1150	1	150	25	39	2250
A9XF20KV1185	1	185	25	41	2600
A9XF20KV1240	1	240	25	44	3150
A9XF20KV1300	1	300	25	46	3800
A9XF20KV1400	1	400	35	49	4750
A9XF20KV1500	1	500	35	52	5800

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²		CURRENT CARRYING CAPACITY IN TREFOIL Amps	
Conductor	Copper Wire Screen	In Ground	In Air
35	16	189	200
50	16	222	239
70	16	271	297
95	16	323	361
120	16	367	416
150	25	409	470
185	25	461	538
240	25	532	634
300	25	599	724
400	35	671	829
500	35	754	953

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.