



JE-H(St)H FE180-E30 Communication Cable



Eland Product Group: B8T

APPLICATION

For signal transmission within systems for measuring, control, data, and regulation technology and for use as an installation cable in fire hazard rooms with a high concentration of people material assets and for installation of fire survival cable systems according to DIN 4102 part 12. For fixed installation in dry and wet rooms.

CHARACTERISTICS

Voltage Rating
225V

Maximum Operating Temperature
Fixed: -5°C to +50°C

Minimum Bending Radius
Fixed: 7.5 x overall diameter

CONSTRUCTION

Conductor
Class 1 Solid Tinned Copper

Insulation
Flame Retardant Non-Corrosive compound

Filler
LSZH (Low Smoke Zero Halogen)

Screen
Plastic Coated Aluminium Foil

Sheath
Flame Retardant Non-Corrosive compound

Core Identification
● Pink ● Orange ● Violet ● Pink ● Orange

Sheath Colour
● Orange

STANDARDS

VDE 0815, DIN 4102, DIN EN 61034/IEC 61034,
DIN EN 50267/IEC 60754

Flame Retardant according to VDE 0482-266-2-4
/IEC 60332-3-24 (Cat. C)

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



FS 672069



EMS 672067



OHS 672066

REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



KM 634267



DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
B8F02000068OR	2	0.8	7.5	76
B8F0400008OR	4	0.8	9.3	130
B8F0800008OR	8	0.8	11.4	232
B8F1200008OR	12	0.8	13.5	318
B8F1600008OR	16	0.8	15	430
B8F2000008OR	20	0.8	16.5	514
B8F3200008OR	32	0.8	19.5	730
B8F4000008OR	40	0.8	22.5	962
B8F5200008OR	52	0.8	25.2	1200

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.