



# Cat 5E 25 Pair U/UTP LSZH Cable



Eland Product Group: A8N

## APPLICATION

High performance 25 pair LSZH backbone cable suitable for 100Base-T, Gigabit Ethernet, 155 Mbps A<sup>TM</sup>, TP-PMD audio, multimedia and telephone networks.

## CHARACTERISTICS

### Temperature Rating

Fixed: -20°C to +60°C

### Minimum Bending Radius

Full load: 20 x overall diameter

No load: 15 x overall diameter

## CONSTRUCTION

### Conductor

Class 1 solid copper conductor

### Insulation

HDPE (High Density Polyethylene)

### Filler

PE (Polyethylene) filler core

### Separator

Mylar tape

### Sheath

LSZH (Low Smoke Zero Halogen)

### Core Identification

- Pair 1: ● White/Blue ● Blue/White
- Pair 2: ● White/Orange ● Orange/White
- Pair 3: ● White/Green ● Green/White
- Pair 4: ● White/Brown ● Brown/White
- Pair 5: ● White/Grey ● Grey/White
- Pair 6: ● Red/Blue ● Blue/Red
- Pair 7: ● Red/Orange ● Orange/Red
- Pair 8: ● Red/Green ● Green/Red
- Pair 9: ● Red/Brown ● Brown/Red
- Pair 10: ● Red/Grey ● Grey/Red
- Pair 11: ● Black/Blue ● Blue/Black
- Pair 12: ● Black/Orange ● Orange/Black
- Pair 13: ● Black/Green ● Green/Black
- Pair 14: ● Black/Brown ● Brown/Black
- Pair 15: ● Black/Grey ● Grey/Black
- Pair 16: ● Yellow/Blue ● Blue/Yellow
- Pair 17: ● Yellow/Orange ● Orange/Yellow
- Pair 18: ● Yellow/Green ● Green/Yellow

### Sheath Colour

- Grey

## STANDARDS

ISO / IEC 11801, TIA 568-B.2-1



## THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



## REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.



- Pair 19: ● Yellow/Brown ● Brown/Yellow
- Pair 20: ● Yellow/Grey ● Grey/Yellow
- Pair 21: ● Purple/Blue ● Blue/Purple
- Pair 22: ● Purple/Orange ● Orange/Purple
- Pair 23: ● Purple/Green ● Green/Purple
- Pair 24: ● Purple/Brown ● Brown/Purple
- Pair 25: ● Purple/Grey ● Grey/Purple



## DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	NOMINAL DIAMETER OF CONDUCTOR mm <sup>2</sup>	NOMINAL THICKNESS OF PAIR INSULATION mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/305m box
A8NCAT5E25PRLS	25	0.51	0.91	12	194

## PERFORMANCE CHARACTERISTICS

FREQUENCY MHz	ATTENUATION dB/100m	NEXT dB	PS-NEXT dB	RL dB	ELFEXT dB	PS-ELFEXT dB/100m	PHASE DELAY ns
1	2	65.3	62.3	20	63.8	60.8	570
4	4.1	56.3	53.3	23	51.8	48.8	552
8	5.8	51.8	48.8	24.5	45.7	42.7	546.73
10	6.5	50.3	47.3	25	43.8	40.8	545.38
16	8.2	47.2	44.4	25	39.7	36.7	543
20	9.3	45.8	42.8	25	37.8	34.8	542.05
25	10.4	44.3	41.3	24.3	35.8	32.8	541.2
31.25	11.7	42.9	39.9	23.6	33.9	30.9	540.44
62.5	17	38.4	35.4	21.5	27.9	24.9	538.55
100	22	35.3	32.3	20.1	23.8	20.8	537.6

## ELECTRICAL CHARACTERISTICS

IMPEDANCE (1-100MHz) ohms	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km
100±15	101.3

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.