

# Centipede Overhead Line ATF Feeder Cable



Eland Product Group: **91**

## APPLICATION

This overhead line aluminium conductor cable is used as ATF feeder cable for overhead line applications.

## CONSTRUCTION

### Conductor

Stranded aluminium conductor according to BS 215

## CABLE STANDARDS

BS EN 50182, BS 215-1

### Network Rail Certificate of Acceptance

No: PA05/05259



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

## CHARACTERISTICS

### Description

'Centipede', 415-AL 1

## DIMENSIONS

ELAND PART NO.	NETWORK RAIL PART NO. / PADS	DRAWING NO.	NOMINAL GROSS SECTIONAL AREA mm <sup>2</sup>	NO. OF STRANDS	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
91/030481	0091/030481	148/752	400	37	3.78	26.46	1145