

Belden 9729 - LSF (Belden Alternative) Cable



Eland Product Group: **A3B**

APPLICATION

Belden 9729 - LSF (Belden Alternative) cable is suitable for CAD/CAM & RS422 applications. This cable is used widely in the security and instrumentation industry, audio and computer applications, where there is a need for screening from external sources.

CONSTRUCTION

Conductor

Class 2 stranded tinned copper conductor

Inner Sheath

PE (Polyethylene)

Drain Wire

Tinned copper

Screen

Aluminium foil

Sheath

LSF (Low Smoke and Fume)

CABLE STANDARDS

RS422, Generally to Belden 9729LSF



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

CHARACTERISTICS

Voltage Rating

300V

Temperature Rating

Fixed: -20°C to +80°C

Core Identification

Pair 1: ● Black ● Red

Pair 2: ● Black ○ White

Sheath Colour

● Grey

DIMENSIONS

ELAND PART NO.	BELDEN ALTERNATIVE	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL THICKNESS OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B9729LSFGR	9729LSF	2	AWG24(7)	0.19	6.1	55

ELECTRICAL CHARACTERISTICS

ELAND PART NO.	BELDEN ALTERNATIVE	CAPACITANCE AT 1kHz pF/m	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
A3B9729LSFGR	9729LSF	50	104.2

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.