

Belden 9841 - LSF (Belden Alternative) Cable



Eland Product Group: **A3B**

APPLICATION

Belden 9841 LSF (Belden Equivalent) cable is a 24 AWG low capacitance cable with a high level of screening. Provides interference free, high speed data transmission suitable for RS485 applications.

CONSTRUCTION

Conductor

Class 2 stranded tinned copper conductor

Inner Sheath

PE (Polyethylene)

Screen

Aluminium polyester foil

Drain Wire

Tinned copper

Braid

TCWB (Tinned Copper Wire Braid)

Sheath

LSF (Low Smoke and Fume)

CABLE STANDARDS

Generally to Belden; 9841LSF, RS485



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

CHARACTERISTICS

Voltage Rating

300V

Temperature Rating

Fixed: -20°C to +80°C

Core Identification

Pair 1: Blue/White White/Blue

Sheath Colour

Grey

DIMENSIONS

ELAND PART NO.	BELDEN ALTERNATIVE	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B9841LSFGR	9841LSF	1	AWG24(7)	0.2	5.9	54

ELECTRICAL CHARACTERISTICS

ELAND PART NO.	BELDEN ALTERNATIVE	CAPACITANCE AT 1kHz pF/m	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
A3B9841LSFGR	9841LSF	41.9	94.1

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.