

Belden 8762 - LSZH 300V (Belden Alternative) Cable



Eland Product Group: **A3B**

APPLICATION

Belden 8762 - LSZH (Belden Alternative) cable is suitable for use in instrumentation, data and audio applications where protection against electrical interference is required. Cables with polyethylene insulation show lower signal loss than those using PVC.

CONSTRUCTION

Conductor

Class 2 stranded tinned copper conductor

Insulation

PE (Polyethylene)

Screen

Aluminium foil

Drain Wire

Tinned copper

Sheath

LSZH (Low Smoke Zero Halogen)

CABLE STANDARDS

Generally to Belden 8762



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

CHARACTERISTICS

Voltage Rating

300V

Temperature Rating

Fixed: -20°C to +70°C

Core Identification

1 Pair: ● Black ● Transparent

Sheath Colour

● Grey

DIMENSIONS

ELAND PART NO.	BELDEN ALTERNATIVE	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B8762LSZH	8762LSZH	1	AWG20(7)	0.3	5.2	38

ELECTRICAL CHARACTERISTICS

VELOCITY RATIO %	IMPEDANCE ohms	CAPACITANCE AT 1kHz pF/m	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km
66	56	88	37.6

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.