



MR SE 1093 Signalling Cable (London Underground)



APPLICATION

Single-core cable with dual-layered insulation designed for use in railway signalling applications.

CHARACTERISTICS

Voltage Rating U_0/U
0.6/1kV

Temperature Rating
-15°C to +90°C

Minimum Bending Radius
2 x overall diameter

CONSTRUCTION

Conductor

Class 2 stranded Tinned copper conductor

Insulation

EPR (Ethylene Propylene)

Sheath

LFH (Low Fire Hazard)

Insulation Identification

○ White

Sheath Colour

● Violet: 0.5mm²

● Red: 1mm²

CABLE THIRD-PARTY ACCREDITATION



London Underground Limited (LUL) certified and listed on the Approved Products Register as meeting the requirements for installation within their network

STANDARDS

MR SE 1093, LUL

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTCL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/85/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NO. OF STRANDS	NOMINAL DIAMETER OF STRANDS mm	MAXIMUM DC RESISTANCE AT 20°C ohms/km	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
SE1093-1X0.5	1	0.5	7	0.3	36.7	2.4	9
SE1093-1X1	1	1	7	0.44	18.2	3	19

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.