

8723 - PE Alternative Cable



Eland Product Group: A3B

APPLICATION

8723 Alternative cable is suitable for instrumentation, computer and security applications, point of sale, control systems, and RS232 applications.

CHARACTERISTICS

Voltage Rating 300V

Temperature Rating Fixed: -20°C to +80°C

CONSTRUCTION

Conductor

Class 2 stranded tinned copper

Insulation

PE (Polyethylene)

Aluminium foil tape

Drain Wire

Stranded tinned copper

Sheath

PE (Polyethylene)

Core Identification

Pair 1:

Black

Red Pair 2: ● Green ○ White

Sheath Colour

Black

THE CABLE LAB® AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions. our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability





BUSINESS 1.5°C





REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.







DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B8723PEBK	2	AWG22(7)	0.24	5.8	30

ELECTRICAL CHARACTERISTICS

AWG (NO. OF STRANDS)	CAPACITANCE AT 1KHZ pF/m	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	
AWG22(7)	114.8	65.3	

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.