



# SSE 6.35/11 (12)kV Three Core Unarmoured Aluminium Conductors



## APPLICATION

Medium voltage DNO aluminium power cable approved to Scottish & Southern Electricity (SSE) specification and manufactured by G81 suppliers for connections from existing grid to new sub-main developments.

## CHARACTERISTICS

**Voltage Rating** (U<sub>0</sub>/U)  
6.35/11 (12)kV

**Temperature Rating**  
0°C to +90°C

## CONSTRUCTION

### Conductor

Class 2 Stranded Aluminium Conductor

### Conductor Screen

Fully bonded semi-conductive compound

### Insulation

XLPE (Cross-Linked Polyethylene)

### Insulation Screen

Semi-conductive compound

### Screen

Copper Wires and Equalising Copper Tape

### Separator

Binding Tape

### Sheath

MDPE (Medium Density Polyethylene)

### Sheath Colour

● Red

## STANDARDS

BS 7870-4.10, SP-PS-076



## ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



F5 672069



EMS 672067

OHS 672066

## REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



KM 634267





## DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	NOMINAL AREA OF METALLIC SCREEN mm <sup>2</sup>	NOMINAL OVERALL DIAMETER OF CABLE (OR TRIPLEX GROUP IF APPLICABLE) mm <sup>2</sup>	NOMINAL WEIGHT OF CABLE (OR TRIPLEX GROUP IF APPLICABLE) kg	MINIMUM BENDING RADIUS mm	MAXIMUM PULLING TENSION N
D200315RD000	3	150	60	61	3280	1160	13500
D200317RD000	3	240	60	70	4380	1340	21600
D200318RD000	3	300	60	75	4990	1440	27000

## ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km	MAXIMUM AC RESISTANCE OF CONDUCTOR AT 20°C ohms/km	REACTANCE AT 50HZ ohms/km	CAPACITANCE µf/km	1 SECOND SHORT CIRCUIT RATING OF CONDUCTOR kA	1 SECOND SHORT CIRCUIT RATING OF METALLIC SCREEN kA
150	0.206	0.265	0.091	0.33	14.2	9.3
240	0.125	0.161	0.085	0.41	22.7	9.3
300	0.100	0.130	0.084	0.44	28.3	9.3

## CURRENT CARRYING CAPACITY

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	DIRECT BURIED Amps	IN DUCTS Amps	IN AIR Amps
150	295	255	335
240	390	340	450
300	435	380	510

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.