



H07G-U Cable



Eland Product Group: B5K

APPLICATION

Single core H07G cable with solid, stranded or flexible stranded copper conductor for internal installations in dry, clean environments requiring a rated voltage of 450/750V. EVA insulation supports a maximum operating temperature of +110°C.

CHARACTERISTICS

Voltage Rating
450/750V

Temperature Rating
Maximum operating temperature: 110°C
Maximum conductor short-circuit temperature: 250°C
Minimum installation temperature: 5°C

CONSTRUCTION

Conductor
Class 1 solid Copper

Insulation
EVA (Ethylene Vinyl Acetate) Rubber EI8 Type

Insulation Colour
● Red ● Black ● Blue ● Orange ○ White ● Yellow
● Green/Yellow ● Grey ● Brown ● Violet ● Pink

STANDARDS

EN 50525-1, 50525-2-42, IEC/EN 60228, IEC 60245-1/2/7, DIN VDE 0282-1/7/300, DIN VDE 0295, VDE 0298-4, EN 50395, EN 50396, HD 22.1/9, HD 308, HD 383, HD 516

Flame Retardant to IEC/EN 60332-1-2

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/853/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NOMINAL CROSS SECTIONAL AREA mm ²	MINIMUM OVERALL DIAMETER mm	MAXIMUM OVERALL DIAMETER mm	NOMINAL CABLE WEIGHT kg/km
B5K**0015	1.5	2.8	3.5	25
B5K**0025	2.5	3.4	4.3	38
B5K**0040	4	4	5	57
B5K**0060	6	4.5	5.6	79
B5K**010	10	5.7	7.1	129

* Designates the sheath colour. For each Eland Cables part number replace with the colour code as listed below: e.g. B5LRD0015 = 1.5mm² Red

COLOUR CODES

COLOUR	Black	Blue	Grey	Green/ Yellow	Orange	Red	Pink	Yellow	Violet	Brown	White
CODE	BK	BL	GR	GY	OR	RD	PK	YW	VI	BR	WH

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.