

Hummel Brass Gland



Eland Product Group: **TER**

APPLICATION

Standard grade nickel-plated brass cable gland from market leader Hummel. Rated IP68 for a seal preventing ingress of dust and water, suitable for immersion. This MS Brass Gland is for use in environments demanding high levels of chemical and mechanical stability including measurement and control applications provided protection against electromagnetic interference. Recommended for interconnection with Veriflex cables

CONSTRUCTION

Gland Material

Nickel plated brass

Seal Insert

NBR (Nitrile Rubber)

Protection


IP68

CHARACTERISTICS

Operating Temperature

Static: -40°C to +100°C

Dynamic: -20°C to +80°C



STANDARDS

IP68

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	AG	MINIMUM/MAXIMUM CABLE RANGE mm	GL mm	NOMINAL OUTER mm	H mm
HUMGECM12MNP000	M 12x 1.5	3 - 6.5	6	14	20
HUMGECM16MNP000	M 16x 1.5	4.5 - 10	6	19	22
HUMGEMC20MNP000	M 20x 1.5	6-12	6	22	25
HUMGECM25MNP000	M 25 x 1.5	9 - 17	7	29	26
HUMGECM32MNP000	M 32 x 1.5	11 -21	8	34	34
HUMGECM40MNP000	M 40x 1.5	19-28	8	44	37
HUMGECM50MNP000	M 50x 1.5	27 - 35	9	54	45
HUMGECM63MNP000	M 63x 1.5	34-48	10	67	48

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.