



EN 50288-7 - RE-2X(st)Y PVC Cable



Eland Product Group: EN

APPLICATION

These cables are designed to connect electrical instrument circuits and provide communication services in and around process plants (e.g. petrochemical industry etc.). Not suitable for direct burial applications.

CHARACTERISTICS

Voltage Rating
300V

Operating Temperature
Fixed: -40°C to +80°C
Flexed: 0°C to +50°C

Minimum Bending Radius
6 x overall diameter

CONSTRUCTION

Conductor
0.5mm² - 0.75mm²: Class 5 flexible copper conductor
1mm² and above: Class 2 stranded copper conductor

Insulation
XLPE (Cross-Linked Polyethylene)

Collective Screen
Al/PET (Aluminium/Polyester Tape)

Drain Wire
Tinned copper

Sheath
PVC (Polyvinyl Chloride) - UV Resistant

Core Identification
Pairs: ○ White ● Black, numbered
Triples: ○ White ● Black ● Red

Outer Sheath Colour
● Blue ● Black

Note
500V rated cables available on request

STANDARDS

EN 50288-7, EN 50288-1, EN 60228

Flame Retardant according to: IEC/EN 60332-1-2,
IEC/EN 60332-3-24
UV Resistant

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NO. OF PAIRS/TRIPLE	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL OVERALL DIAMETER mm
EN01P05AUUCXY**	1P	0.5	4.6
EN01P07AUUCXY**	1P	0.75	4.6
EN01P10AUUCXY**	1P	1	5
EN01P15AUUCXY**	1P	1.5	6.4
EN01T05AUUCXY**	1T	0.5	4.8
EN01T07AUUCXY**	1T	0.75	5.4
EN01T10AUUCXY**	1T	1	5.3
EN01T15AUUCXY**	1T	1.5	6.7
EN02P05AUUCXY**	2P(Q)	0.5	6.7
EN02P07AUUCXY**	2P(Q)	0.75	7.6
EN02P10AUUCXY**	2P(Q)	1	7.5
EN02P15AUUCXY**	2P(Q)	1.5	9.7
EN05P05AUUCXY**	5P	0.5	8.6
EN05P07AUUCXY**	5P	0.75	9.8
EN05P10AUUCXY**	5P	1	9.5
EN05P15AUUCXY**	5P	1.5	12.6
EN10P05AUUCXY**	10P	0.5	11.9
EN10P07AUUCXY**	10P	0.75	13.7
EN10P10AUUCXY**	10P	1	13.4
EN10P15AUUCXY**	10P	1.5	17.9
EN15P05AUUCXY**	15P	0.5	13.8
EN15P07AUUCXY**	15P	0.75	15.9
EN15P10AUUCXY**	15P	1	15.5
EN15P15AUUCXY**	15P	1.5	20.8
EN20P05AUUCXY**	20P	0.5	15.5
EN20P07AUUCXY**	20P	0.75	17.9
EN20P10AUUCXY**	20P	1	17.4
EN20P15AUUCXY**	20P	1.5	23.5

P = Pairs, Q = Quads, T = Triples

* Designates the sheath colour. For each Eland Cables part number replace with the colour code as listed below e.g. EN01P05SAUUCXYBK = 0.5mm² Black

COLOUR CODES

COLOUR	Blue	Black
CODE	BU	BK



CONDUCTORS

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km	
	Class 2	Class 5
0.5	36.36	39.39
0.75	24.8	26.8
1	18.3	19.7
1.5	12.42	13.43
2.5	7.56	8.05

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	MUTUAL CAPACITANCE pF/m	MINIMUM INSULATION RESISTANCE AT 20°C Gohms/km	MAXIMUM L/R RATIO μH/ohms
0.5	75	>10	25
0.75	75	>10	25
1	75	>10	25
1.5	85	>10	40
2.5	85	>10	65

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.