

NTSCGEWÖW 6kV Torsion Power Cable



Eland Product Group: A9K

APPLICATION

Medium voltage cable available in single and multicores suitable for applications under torsional stresses, for energy transmission and loop applications. Oil, ozone and UV resistant.

CHARACTERISTICS

Rated Voltage Uo/U
3.6/6kV

Temperature Rating
-40°C +90°C

Minimum Bending Radius
10x Overall Diameter

Torsion Application
±100°/m

CONSTRUCTION

Conductor
Stranded Tinned Copper Wires

Insulation
Special EPR (Ethylene Propylene Rubber)

Outer Sheath
CM/CR (ChloroPolyethylene / Polychloroprene)

Sheath Colour
● Black

DIMENSIONS

ELAND PART NUMBER	NUMBER OF CORES	NOMINAL CROSS SECTIONAL AREA SIZE mm ²	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A9K03035/35BK	1	240	42.8	3100
A9K03050/50BK	1	300	44.9	3800
A9K03070/70BK	3	35/35	61.0	5723
A9K03095/95BK	3	50/50	69.0	6596
A9K01240BK	3	70/70	73.0	7881
A9K01300BK	3	35/95	80.0	10612

STANDARDS

DIN VDE 0250-813, DIN VDE 0295

THE CABLE LAB®

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/85/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.

