

# NA2XSYPVC Aluminium Conductor XLPE PVC - 18/30 (36)kV Cable



Eland Product Group: A9X

## APPLICATION

To be laid directly in ground, outdoors, indoors and in cable ducts. Medium voltage cables for distribution networks, also for connection to generation units and plant and process connection.

## CHARACTERISTICS

**Voltage Rating**  $U_0/U$  ( $U_m$ )  
18/30 (36)kV

**Temperature Rating**  
Fixed: -20°C to +90°C

**Minimum Bending Radius**  
15 x overall diameter

## CONSTRUCTION

**Conductor**  
Class 2 stranded aluminium conductor

**Conductor Screen**  
Semi-conductive material

**Insulation**  
XLPE (Cross-Linked Polyethylene)

**Insulation Screen**  
Semi-conductive material

**Screen**  
Copper wires

**Sheath**  
PVC (Polyvinyl Chloride)

**Sheath Colour**  
● Red

## STANDARDS

EN 60228, IEC 60502-2

Flame retardant according to IEC/EN 60332-1-2

## THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



## REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.





## DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>		NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
		Conductor	Copper Wire Screen		
A9XA30KV1050	1	50	16	41	1190
A9XA30KV1070	1	70	16	42	1315
A9XA30KV1095	1	95	16	43	1450
A9XA30KV1120	1	120	16	45	1580
A9XA30KV1150	1	150	25	47	1800
A9XA30KV1185	1	185	25	49	1965
A9XA30KV1240	1	240	25	51	2230
A9XA30KV1300	1	300	25	53	2470
A9XA30KV1400	1	400	35	56	2920

## ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>		CURRENT CARRYING CAPACITY Amps	
Conductor	Copper Wire Screen	In Trefoil	
		In Ground	In Air
50	16	175	187
70	16	214	232
95	16	256	281
120	16	290	323
150	25	324	365
185	25	366	418
240	25	426	494
300	25	479	564
400	35	545	654

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.