



## LXHIOAE 18/30kV Cable



Eland Product Group: MP51

### APPLICATION

Portuguese reference Medium Voltage cable for power distribution and power supply stations used in Utility and Industrial applications, for rated voltages up to 18/30kV. Suitable for fixed installations, directly buried. Good mechanical protection.

### CHARACTERISTICS

**Voltage Rating** U<sub>o</sub>/U (U<sub>m</sub>)  
18/30 (36)kV

**Temperature Rating**  
Conductor maximum operating temperature: 90°C  
Maximum short-circuit temperature: 250°C

**Minimum Bending Radius**  
During installation: 15 x overall diameter  
After installation: 10 x overall diameter

### CONSTRUCTION

**Conductor**  
Class 2 stranded Aluminium,

**Conductor Screen**  
Semi-conductive XLPE (Cross-Linked Polyethylene)

**Insulation**  
XLPE (Cross-Linked Polyethylene)

**Insulation Screen**  
Semi-conductive XLPE (Cross-Linked Polyethylene)

**Metallic Screen**  
Copper wire screen

**Tape**  
Plastic tape is applied over the screen

**Filler**  
Extruded polymeric material

**Bedding**  
PE (Polyethylene)

**Armour**  
STA (Steel Tape Armoured)

**Sheath**  
PE (Polyethylene) type ST7

**Sheath Colour**  
● Black

### STANDARDS

IEC 60228, IEC 60502-2

### ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



FS 672069



EMS 672067



OHS 672066

### REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



KN 036287



## DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP5130KV03050	3	50	26.0	76.0	6700
MP5130KV03070	3	70	27.5	80.0	7445
MP5130KV03095	3	95	29.5	85.5	9015
MP5130KV03120	3	120	31.0	89.5	9895
MP5130KV03150	3	150	32.5	92.5	10515
MP5130KV03185	3	185	34.0	96.0	11420
MP5130KV03240	3	240	36.0	101.5	12750
MP5130KV03300	3	300	39.0	108.0	14320
MP5130KV03400	3	400	42.0	115.0	16220

## ELECTRICAL CHARACTERISTICS

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
3	50	159	162	4.7	0.6410	0.45	0.14
3	70	196	198	6.6	0.4430	0.41	0.16
3	95	238	236	9.0	0.3200	0.39	0.17
3	120	274	268	11.3	0.2530	0.38	0.19
3	150	309	302	14.2	0.2060	0.37	0.20
3	185	354	342	17.5	0.1640	0.35	0.21
3	240	415	395	22.7	0.1250	0.34	0.24
3	300	472	444	28.3	0.1000	0.32	0.26
3	400	545	504	37.8	0.0778	0.31	0.29

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.