

400Hz Airport 4-core With Control Wires Cable



Eland Product Group: F19

APPLICATION

These 4-core cables with control wires are designed for 400Hz systems for power supply of aircraft, computer systems and radar stations. They are suitable for laying in earth, in water, outdoors, indoors and in cable ducts.

CHARACTERISTICS

Rated Voltage U₀/U (Um)

0.6/1kV

Temperature Rating

Fixed: -40°C to +90°C

Minimum Bending Radius

Static: 4x Overall Diameter
 Dynamic: 5x Overall Diameter

CONSTRUCTION

Conductor

Class 5/Class 6 Stranded copper conductor

Insulation

XLEPR (Cross-linked Ethylene Propylene Rubber)

Control Core

1mm² stranded copper conductor with Polyolefin insulation

Sheath

PUR (Polyurethane)

Sheath Colour

● Yellow

DIMENSIONS

ELAND PART NO.	NUMBER OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NO. CONTROL CORES	NOMINAL DIAMETER SINGLE CORE mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
F19LV04035YW	4	35	4	13.7	33.0	2600
F19LV04050YW	4	50	4	18.2	44.0	3900
F19LV04070YW	4	70	4	21.2	51.3	4300
F19LV04120YW	4	120	4	23.2	56.0	7400

STANDARDS

VDE 0295, IEC 60228

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].

