

PAS BS 5308 Part 2 Type 1 PVC/CAM/PVC Cable



Eland Product Group: I

APPLICATION

Publicly Available Standard (PAS) BS 5308 cables are designed to carry communication and control signals in a variety of installation types including the petrochemical industry. The signals can be of analogue, data or voice type and from a variety of transducers such as pressure, proximity or microphone. Part 2 Type 1 cables are generally designed for indoor use and in environments where mechanical protection is not required.

CHARACTERISTICS

Voltage Rating (Uo/U)
300/500V

Temperature Rating
Fixed: -40°C to +80°C
Flexed: 0°C to +50°C

Minimum Bending Radius
Fixed: 6 x overall diameter

CONSTRUCTION

Conductor
0.5mm² - 0.75mm²: Class 5 flexible copper conductor
1mm² and above: Class 2 stranded copper conductor

Insulation
PVC (Polyvinyl Chloride)

Screen
Al/PET (Aluminium/Polyester Tape)

Drain Wire
Tinned copper

Sheath
PVC (Polyvinyl Chloride)

Sheath Colour
● Blue ● Black

STANDARDS

BS/PAS 5308, EN 60228

Flame Retardant according to: IEC/EN 60332-1-2,
IEC/EN 60332-3-24

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/865/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.





DIMENSIONS

ELAND PART NO.	NO. OF PAIRS/TRIPLE	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL OVERALL DIAMETER mm
I0105P2T1CP**	1P	0.5	7
I0175P2T1CP**	1P	0.75	7.4
I0110P2T1CP**	1P	1	7.4
I0115P2T1CP**	1P	1.5	8.3
I0125P2T1CP**	1P	2.5	9.1
I1T05P2T1CP**	1T	0.5	7.3
I1T75P2T1CP**	1T	0.75	7.7
I1T10P2T1CP**	1T	1	7.7
I1T15P2T1CP**	1T	1.5	8.9
I1T25P2T1CP**	1T	2.5	9.7
I0205P2T1CP**	2P(Q)	0.5	7.9
I0275P2T1CP**	2P(Q)	0.75	8.4
I0210P2T1CP**	2P(Q)	1	8.4
I0215P2T1CP**	2P(Q)	1.5	9.7
I0225P2T1CP**	2P(Q)	2.5	10.7
I0505P2T1CP**	5P	0.5	13.1
I0575P2T1CP**	5P	0.75	13.8
I0510P2T1CP**	5P	1	14.2
I0515P2T1CP**	5P	1.5	16.4
I0525P2T1CP**	5P	2.5	18.2
I1005P2T1CP**	10P	0.5	17.2
I1075P2T1CP**	10P	0.75	18.9
I1010P2T1CP**	10P	1	18.4
I1015P2T1CP**	10P	1.5	21.6
I1025P2T1CP**	10P	2.5	25.1
I1505P2T1CP**	15P	0.5	19.8
I1575P2T1CP**	15P	0.75	21.9
I1510P2T1CP**	15P	1	21.3
I1515P2T1CP**	15P	1.5	25.4
I1525P2T1CP**	15P	2.5	29.2
I2005P2T1CP**	20P	0.5	22.3
I2075P2T1CP**	20P	0.75	24.6
I2010P2T1CP**	20P	1	24.4
I2015P2T1CP**	20P	1.5	28.5
I2025P2T1CP**	20P	2.5	39.8

* Designates the sheath colour. For each Eland Cables part number replace with the colour code

P = Pairs
Q = Quad
T = Triple



Click here for more information:

elandcables.com | [PAS BS 5308 P2 T1 PVC/CAM/PVC Cable](#)

ELAND
CABLES

CONDUCTORS

NOMINAL CROSS SECTIONAL AREA mm ²	CONDUCTOR CLASS	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km
0.5	5	39
0.75	5	26
1	1	18.1
1.5	2	12.1
2.5	2	7.41

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	MUTUAL CAPACITANCE pF/m		MINIMUM INSULATION RESISTANCE AT 20°C mohms/km	MAXIMUM L/R RATIO μH/ohms
	Between Pairs or Adjacent Cores	Between any Core and Screen		
0.5	250	450	>25	25
0.75	250	450	>25	25
1	250	450	>25	25
1.5	250	450	>25	40
2.5	250	450	>25	65

CORE IDENTIFICATION

PAIR NO.	A WIRE	B WIRE
1	○ White	● Blue
2	○ White	● Orange
3	○ White	● Green
4	○ White	● Brown
5	○ White	● Grey
6	● Red	● Blue
7	● Red	● Orange
8	● Red	● Green
9	● Red	● Brown
10	● Red	● Grey
11	● Black	● Blue
12	● Black	● Orange
13	● Black	● Green
14	● Black	● Brown
15	● Black	● Grey
16	● Yellow	● Blue
17	● Yellow	● Orange
18	● Yellow	● Green
19	● Yellow	● Brown
20	● Yellow	● Grey
21	● White/Blue	● Blue
22	● White/Blue	● Orange
23	● White/Blue	● Green
24	● White/Blue	● Brown
25	● White/Blue	● Grey
26	● Red/Blue	● Blue
27	● Red/Blue	● Orange



PAIR NO.	A WIRE	B WIRE
28	Red/Blue	Green
29	Red/Blue	Brown
30	Red/Blue	Grey
31	Blue/Black	Blue
32	Blue/Black	Orange
33	Blue/Black	Green
34	Blue/Black	Brown
35	Blue/Black	Grey
36	Yellow/Blue	Blue
37	Yellow/Blue	Orange
38	Yellow/Blue	Green
39	Yellow/Blue	Brown
40	Yellow/Blue	Grey
41	White/Orange	Blue
42	White/Orange	Orange
43	White/Orange	Green
44	White/Orange	Brown
45	White/Orange	Grey
46	Orange/Red	Blue
47	Orange/Red	Orange
48	Orange/Red	Green
49	Orange/Red	Brown
50	Orange/Red	Grey

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.