

LiYCY TCWB Screened TP (Twisted Pair) PVC Control Cable



Eland Product Group: A5C

APPLICATION

To be installed in dry and humid rooms and used as a termination and connection cable in the control, measuring and signal technology.

CHARACTERISTICS

Voltage Rating

0.14mm²: 350V
Above 0.14mm²: 500V

Test Voltage

0.14mm²: 800V
Above 0.14mm²: 1200V

Temperature Rating

Fixed: -40°C to +80°C
Flexed: +5°C to +50°C

Minimum Bending Radius

Fixed: 10 x overall diameter

CONSTRUCTION

Conductor

Fine-stranded copper conductor

Insulation

PVC (Polyvinyl Chloride)

Separator

Plastic foil tape

Screen

TCWB (Tinned Copper Wire Braid)

Sheath

PVC (Polyvinyl Chloride)

Core Identification

Pair 1: ○ White ● Brown
Pair 2: ● Green ● Yellow
Pair 3: ● Grey ● Pink
Pair 4: ● Blue ● Red
Pair 5: ● Black ● Violet
Pair 6: ● Grey/Pink ● Red/Blue
Pair 7: ● White/Green ● Brown/Green
Pair 8: ● White/Yellow ● Yellow/Brown
Pair 9: ● White/Grey ● Grey/Brown
Pair 10: ● White/Pink ● Pink/Brown

Outer Sheath Colour

● Grey

STANDARDS

DIN VDE 0812

Flame Retardant according to: IEC/EN 60332-1-2

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved prod



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.





DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	NOMINAL CROSS SECTIONAL AREA mm ²	CONDUCTOR CONSTRUCTION		CONDUCTOR LOOP RESISTANCE ohms/km	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
			No. of strands	Strand Diameter mm			
A5CT200014	2	0.14	18	0.1	276	5.8	34
A5CT200025	2	0.25	14	0.16	151	6.6	46
A5CT200034	2	0.34	19	0.16	115	7.5	64
A5CT20050	2	0.5	16	0.21	75.6	8.2	75
A5CT20075	2	0.75	24	0.21	50.6	8.6	106
A5CT300014	3	0.14	18	0.1	276	6.2	43
A5CT300025	3	0.25	14	0.16	151	7	64
A5CT300034	3	0.34	19	0.16	115	7.9	86
A5CT30050	3	0.5	16	0.21	75.6	8.7	98
A5CT30075	3	0.75	24	0.21	50.6	9.5	140
A5CT400014	4	0.14	18	0.1	276	6.8	50
A5CT400025	4	0.25	14	0.16	151	7.6	73
A5CT400034	4	0.34	19	0.16	115	8.5	113
A5CT40050	4	0.5	16	0.21	75.6	9.3	123
A5CT40075	4	0.75	24	0.21	50.6	10.8	179
A5CT500014	5	0.14	18	0.1	276	7.7	70
A5CT500025	5	0.25	14	0.16	151	8.4	88
A5CT600014	6	0.14	18	0.1	276	7.9	81
A5CT600025	6	0.25	14	0.16	151	8.6	98
A5CT60050	6	0.5	16	0.21	75.6	10.8	162
A5CT60075	6	0.75	24	0.21	50.6	12.5	246
A5CT800014	8	0.14	18	0.1	276	8.6	93
A5CT800025	8	0.25	14	0.16	151	9.4	118
A5CT80050	8	0.5	16	0.21	75.6	11.8	190
A5CT80075	8	0.75	24	0.21	50.6	14.6	300
A5CT1000014	10	0.14	18	0.1	276	9.5	115
A5CT1000025	10	0.25	14	0.16	151	10.7	165
A5CT1200014	12	0.14	18	0.1	276	9.9	125
A5CT120050	12	0.5	16	0.21	75.6	14	342
A5CT12075	12	0.75	24	0.21	50.6	17.8	433
A5CT1600014	16	0.14	18	0.1	276	11.2	148
A5CT16075	16	0.75	24	0.21	50.6	18.7	564

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	ATTENUATION AT 800Hz db/km	MUTUAL CAPACITANCE
0.14	2.3	120
0.25	1.9	120
0.34	1.5	120
0.5	1.3	120
0.75	1.1	120

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.