



BS 7211 624-B Twin and Earth LSZH Cable



Eland Product Group: A9B

APPLICATION

Installation in walls, on boards and in channels or embedded in plaster. For installations where fire, smoke emissions and toxic fumes create a potential risk to life and equipment.

CHARACTERISTICS

Voltage Rating U_o/U
300/500V

Temperature Rating
+5°C to +70°C

Minimum Bending Radius
3 x overall diameter

CONSTRUCTION

Conductor

1mm² to 2.5mm²: Class 1 solid conductor
4mm² to 10mm²: Class 2 stranded conductor

Circuit Protection Conductor (Earth)

1mm² to 2.5mm²: Class 1 solid copper conductor
4mm² to 16mm²: Class 2 stranded copper conductor

Insulation

XLPE (Cross-Linked Polyethylene)

Sheath

LSZH (Low Smoke Zero Halogen)

Insulation Colour

2 core: ● Blue ● Brown
3 core: ● Brown ● Black ● Grey

Sheath Colour

○ White

CABLE THIRD-PARTY ACCREDITATION



Cables are tested and accredited by BASEC, The British Approvals Service for Cables

STANDARDS

BS7211, EN 60228

Flame Retardant according to BS EN/IEC 60332-1-2
Low Smoke Halogen Free according to IEC/EN 60754-1/2, IEC/EN 61034-1/2

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



FS 672069



EMS 672067



OHS 672066

REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



XM 634267





DIMENSIONS

ELAND PART NO.	NO. OF CORES	CONDUCTOR CLASS	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL THICKNESS OF INSULATION mm	NOMINAL THICKNESS OF SHEATH mm	NOMINAL OVERALL DIMENSIONS mm
A9B02010WH	2	1	1	0.6	0.9	4.8 x 8.4
A9B02015WH	2	1	1	0.7	0.9	4.8 x 9.2
A9B02025WH	2	1	1.5	0.8	1	5.7 x 10.5
A9B02040WH	2	2	1.5	0.8	1	6.1 x 11.7
A9B02060WH	2	2	2.5	0.8	1.1	6.9 x 13.6
A9B0210WH	2	2	4	1	1.2	8.1 x 16.2
A9B03010WH	3	1	1	0.6	0.9	4.7 x 11
A9B03015WH	3	1	1	0.7	0.9	4.9 x 11.8
A9B03025WH	3	1	1	0.8	1	5.6 x 13.3
A9B03040WH	3	2	1.5	0.8	1	6.2 x 15.7

CONDUCTORS

Class 1 Copper Conductor for Single and Multi-Core Cables

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
	Plain Wires
1	18.1
1.5	12.1
2.5	7.41
4	4.61
6	3.08
10	1.83

ELECTRICAL CHARACTERISTICS

Current Carrying Capacity

NOMINAL CROSS SECTIONAL AREA mm ²	REFERENCE METHOD A* (IN CONDUIT IN WALL) Amps	REFERENCE METHOD C* (CLIPPED DIRECT) Amps	VOLTAGE DROP mV/A/m
1	11.5	16	44
1.5	14.5	20	29
2.5	20	27	18
4	26	37	11
6	32	47	7.3
10	44	64	4.4
16	57	85	2.8

The above table is in accordance with 4D5 of the 18th Edition of IEE Wiring Regulations BS7671 and IEC 60364-5-52

Note

A* For full installation method refer to Table 4A2 Installation Method 2 but for flat twin and earth cable of the 18th Edition of IEE Wiring Regulations.

C* For full installation method refer to Table 4A2 Installation Method 20 but for flat twin and earth cable of the 18th Edition of IEE Wiring Regulations.

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.