

# Cat 5E U/UTP SWA LSZH Cable



Eland Product Group: A8N

## APPLICATION

An armoured multi-pair high performance cable that consists of twisted pairs, used mainly for data transmission. Category 5E cables support a frequency range of up to 100MHz and designed for transmission speeds of up to 1 gigabit per second (Gigabit Ethernet). For installations where fire, smoke emissions and toxic fumes create a potential risk to life and equipment.

## CHARACTERISTICS

### Temperature Rating

-20°C to +60°C

### Minimum Bending Radius

Fixed: 8 x overall diameter

## CONSTRUCTION

### Conductor

Class 1 solid copper conductor

### Insulation

HDPE (High Density Polyethylene)

### Inner Sheath 1

LSZH (Low Smoke Zero Halogen)

### Inner Sheath 2

LSZH (Low Smoke Zero Halogen)

### Armour

SWA (Steel Wire Armour)

### Sheath

LSZH (Low Smoke Zero Halogen)

### Core Identification

Pair 1: ● Blue ● White/Blue  
 Pair 2: ● Orange ● White/Orange  
 Pair 3: ● Green ● White/Green  
 Pair 4: ● Brown ● White/Brown

### Sheath Colour

● Black

## STANDARDS

ISO/IEC 11801, TIA 568 C.2

Flame Retardant according to BS EN/IEC 60332-1-2



## THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



## REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.





## DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	AWG	STRAND DIAMETER mm	NOMINAL OVERALL DIAMETER mm
A8NCAT5EUTPSWA	4	24	0.51	12.8

## PERFORMANCE CHARACTERISTICS

FREQUENCY MHz	ATTENUATION dB/100m	NEXT dB	PS-NEXT dB	RL dB	ELFEXT dB	PS-ELFEXT dB/100m	PHASE DELAY ns
1	2	65.3	62.3	20	63.8	60.8	570
4	4.1	56.3	53.3	23	51.8	48.8	552
8	5.8	51.8	48.8	24.5	45.7	42.7	546.73
10	6.5	50.3	47.3	25	43.8	40.8	545.38
16	8.2	47.2	44.4	25	39.7	36.7	543
20	9.3	45.8	42.8	25	37.8	34.8	542.05
25	10.4	44.3	41.3	24.3	35.8	32.8	541.2
31.25	11.7	42.9	39.9	23.6	33.9	30.9	540.44
62.5	17	38.4	35.4	21.5	27.9	24.9	538.55
100	22	35.3	32.3	20.1	23.8	20.8	537.6

## ELECTRICAL CHARACTERISTICS

IMPEDANCE (1-100MHz) ohms	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	VELOCITY RATIO %
100±15	<96.5	65

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.