

NA2XSYPVC Aluminium Conductor XLPE PVC - 18/30 (36)kV Cable



Eland Product Group: A9X

APPLICATION

To be laid directly in ground, outdoors, indoors and in cable ducts. Medium voltage cables for distribution networks, also for connection to generation units and plant and process connection.

CHARACTERISTICS

Voltage Rating U_0/U (Um)
18/30 (36)kV

Temperature Rating
Fixed: -20°C to +90°C

Minimum Bending Radius
15 x overall diameter

CONSTRUCTION

Conductor
Class 2 stranded aluminium conductor

Inner Semi-Conductive Layer
Semi-conductive material

Insulation
XLPE (Cross-Linked Polyethylene)

Outer Semi-Conductive Layer
Semi-conductive material

Screen
Copper wires

Sheath
PVC (Polyvinyl Chloride)

Sheath Colour
● Red

STANDARDS

DIN VDE 0276-620, HD 620, EN 60228, IEC 60502-2

Flame retardant according to IEC/EN 60332-1-2

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECIEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



SCIENCE
BASED
TARGETS

BUSINESS
AMBIITION FOR 1.5°C



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²		NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
		Conductor	Copper Wire Screen		
A9XA30KV1050	1	50	16	41	1190
A9XA30KV1070	1	70	16	42	1315
A9XA30KV1095	1	95	16	43	1450
A9XA30KV1120	1	120	16	45	1580
A9XA30KV1150	1	150	25	47	1800
A9XA30KV1185	1	185	25	49	1965
A9XA30KV1240	1	240	25	51	2230
A9XA30KV1300	1	300	25	53	2470
A9XA30KV1400	1	400	35	56	2920

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²		CURRENT CARRYING CAPACITY Amps	
Conductor	Copper Wire Screen	In Trefoil	
		In Ground	In Air
50	16	175	187
70	16	214	232
95	16	256	281
120	16	290	323
150	25	324	365
185	25	366	418
240	25	426	494
300	25	479	564
400	35	545	654

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.