

8723 - LSZH 300V Alternative Cable



Eland Product Group: A3B

APPLICATION

8723 - LSZH Alternative cable is suitable for instrumentation, computer and security applications, point of sale, control and systems applications.

CHARACTERISTICS

Voltage Rating

300V

Temperature Rating

Fixed: -20°C to +80°C

CONSTRUCTION

Conductor

Class 2 stranded tinned copper

Insulation

PE (Polyethylene)

Aluminium foil tape

Drain Wire

Stranded tinned copper

U.V resistant LSZH (Low Smoke Zero Halogen)

Core Identification

Pair 1:

Black

Red Pair 2: ■ Green ○ White

Sheath Colour

Grey

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions. our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability





SCIENCE BASED TARGETS BUSINESS 1.5°C







REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.







DIMENSIONS

ELAND PART NO.	NO. OF	AWG	NOMINAL DIAMETER	NOMINAL OVERALL	NOMINAL
	PAIRS	(NO. OF STRANDS)	OF STRANDS	DIAMETER	WEIGHT
			mm	mm	kg/km
A3B8723LSZHGR	2	AWG22(7)	0.24	4.2	30

ELECTRICAL CHARACTERISTICS

VELOCITY PROPAGATION %	IMPEDANCE ohms	CAPACITANCE AT 1KHZ	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
66	45	115	54.2

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.