

# Belden 9730 - LSF (Belden Alternative) Cable



Eland Product Group: **A3B**

## APPLICATION

Belden 9730 - LSF (Belden Alternative) cable is suitable for CAD/CAM & RS422 applications. This cable is used widely in the security and instrumentation industry, audio and computer applications, where there is a need for screening from external sources.

## CABLE STANDARDS

RS422, Generally to Belden 9730LSF



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed

## CONSTRUCTION

### Conductor

Stranded tinned copper conductor

### Inner Sheath

PE (Polyethylene)

### Individual Screen

Aluminium foil tape

Drain wire stranded tinned copper

### Sheath

LSF (Low Smoke and Fume)

## CHARACTERISTICS

### Voltage Rating

300V

### Temperature Rating

Fixed: -20°C to +80°C

### Core Identification

Pair 1: ● Black ● Red

Pair 2: ● Black ○ White

Pair 3: ● Black ● Green

### Sheath Colour

● Grey

## DIMENSIONS

ELAND PART NO.	BELDEN ALTERNATIVE	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL THICKNESS OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B9730LSFGR	9730LSF	3	AWG24(7)	0.2	8.48	68

## ELECTRICAL CHARACTERISTICS

ELAND PART NO.	BELDEN ALTERNATIVE	CAPACITANCE AT 1kHz pF/m	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
A3B9730LSFGR	9730LSF	50	94.1

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.

## DIMENSIONS

ELAND PART NO.	BELDEN ALTERNATIVE	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL THICKNESS OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B9730LSFGR	9730LSF	3	AWG24(7)	0.2	8.48	68

## ELECTRICAL CHARACTERISTICS

ELAND PART NO.	BELDEN ALTERNATIVE	CAPACITANCE AT 1kHz pF/m	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
A3B9730LSFGR	9730LSF	50	94.1