

9536 PVC - LSF Alternative Cable



ELAND CAELES ©

THE CABLE LAB®

17025

We are on a journey to Net Zero.

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

through a continuous and rigorous testing regime.

SUSTAINABILITY COMMITMENT

Compact Sustainable Development Goals.

REGULATORY COMPLIANCE

Products Regulation.

IECEE

TARGETS

Our world-class testing facility assures the quality and compliance of this cable

We've committed to near-term emissions reductions and a net-zero target with the

Science Based Targets initiative and we're a signatory to the United Nations Global

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability

This cable is compliant with European Regulation EN 50575, the Construction

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS

compliance has been tested and confirmed by The Cable Lab®.

BASED BUSINESS 1.5°C

ECEE BTL

Eland Product Group: A3B

APPLICATION

9536 - PVC-LSF Alternative cable RS232 data cable is a general purpose overall screened cable. With protection against electrical interference, this cable is suitable for RS232 applications.

CHARACTERISTICS

Voltage Rating 300V

Temperature Rating Fixed: -20°C to +80°C

CONSTRUCTION

Conductor Class 2 stranded tinned copper conductor

Insulation PVC (Polyvinyl Chloride)

Drain Wire Al/Foil (Aluminium Foil)

Screen **Tinned Copper**

Sheath PVC-LSF (Polyvinyl Chloride-Low Smoke Fume)

Core Identification 🕨 Red ● Black 🔾 White ● Green ● Brown ● Blue

Sheath Colour

Grey

ELAND PART NO.	NO. OF CORES	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B9536LSFGR	6	AWG24(7)	0.2	4.7	37

CAPACITANCE AT 1kHz	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C
pF/m	ohms/km
107	94.1

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.

UK T 020 7241 8787 | F 020 7241 8700 | sales@elandcables.com | www.elandcables.com International T +44 20 7241 8740 | F +44 20 7241 8700 | international@elandcables.com

technicalspecification | 1 of 1