



8761 600V LSZH Alternative Cable



Eland Product Group: A3B

APPLICATION

A single pair overall screened LSZH (Low Smoke Zero Halogen) cable, suitable for use in instrumentation, data and audio applications where protection from electrical interference is required. For installations where fire, smoke emissions and toxic fumes create a potential risk to life and equipment.

CHARACTERISTICS

Voltage Rating
600V

Temperature Rating
-25°C to +90°C

CONSTRUCTION

Conductor

Class 2 stranded tinned copper conductor

Insulation

HDPE (High Density Polyethylene)

Shield

Al/PET (Aluminium/Polyester Tape)

Drain Wire

Tinned copper

Sheath

LSZH (Low Smoke Zero Halogen)

Core Identification

● Black ○ White

Sheath Colour

● Violet

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/853/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B8761NH600V	2	AWG22(7)	5.1	26

ELECTRICAL CHARACTERISTICS

MAXIMUM CAPACITANCE pF/m	IMPEDANCE ohms	VELOCITY RATIO %	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
130	64	66	57.4