



# Cat 5E F/UTP LSZH Cable



Eland Product Group: A8N

## APPLICATION

A 4 pair high performance cable that consists of twisted pair conductors, used mainly for data transmission. Category 5E supports a frequency range of up to 100MHz and is designed for transmission speeds of up to 1 gigabit per second (Gigabit Ethernet).

## CHARACTERISTICS

### Temperature Rating

Fixed: -20°C to +60°C

### Minimum Bending Radius

Fixed: 4 x overall diameter  
Flexed: 8 x overall diameter

## CONSTRUCTION

### Conductor

Class 1 solid copper conductor

### Insulation

HDPE (High Density Polyethylene)

### Drain Wire

Tinned copper

### Screen

Aluminium foil

### Sheath

LSZH (Low Smoke Zero Halogen)

### Core Identification

Pair 1: ● Blue ● White/Blue  
Pair 2: ● Orange ● White/Orange  
Pair 3: ● Green ● White/Green  
Pair 4: ● Brown ● White/Brown

### Sheath Colour

● Violet

## STANDARDS

ISO/IEC 11801, TIA 568C.2, YD/T1019

Flame Retardant according to BS EN/IEC 60332-1-2



## ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



FS 672069



EMS 672067



OHS 672066

## REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



XM 634367





## DIMENSIONS

ELAND PART NO.	NO. OF PAIRS (24 AWG)	NOMINAL DIAMETER OVER INSULATION mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/305m box
A8NFORCE5EFTPLS	4	1	5.8	14

## PERFORMANCE CHARACTERISTICS

FREQUENCY MHz	ATTENUATION dB/100m	NEXT dB	PS-NEXT dB	RL dB	ELFEXT dB	PS-ELFEXT dB/100m	PHASE DELAY ns
1	2	65.3	62.3	20	63.8	60.8	570
4	4.1	56.3	53.3	23	51.8	48.8	552
8	5.8	51.8	48.8	24.5	45.7	42.7	546.73
10	6.5	50.3	47.3	25	43.8	40.8	545.38
16	8.2	47.2	44.4	25	39.7	36.7	543
20	9.3	45.8	42.8	25	37.8	34.8	542.05
25	10.4	44.3	41.3	24.3	35.8	32.8	541.2
31.25	11.7	42.9	39.9	23.6	33.9	30.9	540.44
62.5	17	38.4	35.4	21.5	27.9	24.9	538.55
100	22	35.3	32.3	20.1	23.8	20.8	537.6

## ELECTRICAL CHARACTERISTICS

IMPEDANCE (1-100MHz) ohms	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	MAXIMUM RESISTANCE UNBALANCE %
100±15	95	5

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.