




# LFH Rolling Stock Part 6 Type I Cable (London Underground)



ELAND CABLES ©

## APPLICATION

Reduced wall single core cable for use in rolling stock

## CHARACTERISTICS

**Voltage Rating** Uo/U  
0.6/1kV

**Temperature Rating**  
-30°C to +85°C

**Minimum Bending Radius**  
2 x overall diameter

## CONSTRUCTION

### Conductor

Class 2 stranded tinned copper conductor

### Insulation

Reduced wall LFH (Limited Fire Hazard)

### Insulation Colour

● Red

## CABLE THIRD-PARTY ACCREDITATION



London Underground Limited (LUL) certified and listed on the Approved Products Register as meeting the requirements for installation within their network

## STANDARDS

RSE/STD/024 Part 6 Type 1  
Flame Propagation according to 1-085

## THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



SCIENCE  
BASED  
TARGETS

**BUSINESS  
AMBITION FOR 1.5°C**



## REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup> as meeting the requirements of the BSI RoHS Trusted Kitemark<sup>™</sup>.



## DIMENSIONS

| ELAND PART NO. | NO. OF CORES | NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup> | NO. OF STRANDS | NOMINAL DIAMETER OF STRANDS mm | MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km | NOMINAL OVERALL DIAMETER mm | NOMINAL WEIGHT kg/km |
|----------------|--------------|--|----------------|--------------------------------|--|-----------------------------|----------------------|
| LULP6T11X0.5   | 1            | 0.5  | 19             | 0.18                           | 39.7   | 1.5                         | 7                    |
| LULP6T11X0.75  | 1            | 0.75   | 37             | 0.16                           | 25.8   | 1.8                         | 9                    |
| LULP6T11X1     | 1            | 1  | 37             | 0.18                           | 20.4   | 1.9                         | 11                   |
| LULP6T11X1.5   | 1            | 1.5  | 37             | 0.23                           | 12.5   | 2.3                         | 17                   |
| LULP6T11X2.5   | 1            | 2.5  | 37             | 0.3                            | 7.33   | 2.8                         | 28                   |
| LULP6T11X4     | 1            | 4  | 37             | 0.37                           | 4.68   | 3.4                         | 42                   |

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.