



Click here for more information:
elandcables.com | [SE 0875 Cable](#)

**ELAND[®]
CABLES**

SE 0875 Screened Track Crossing Cable (London Underground)



APPLICATION

This cable is for use in Signal Safety Circuits where these are required to cross the track at Ballast level. For installations where fire, smoke emissions and toxic fumes create a potential risk to life and equipment.

CHARACTERISTICS

Voltage Rating
450/750V

Temperature Rating
-15°C to +85°C

Minimum Bending Radius
6 x overall diameter

CONSTRUCTION

Conductor
Class 5 Flexible tinned copper conductor

Insulation
LSZH (Low Smoke Zero Halogen)

Screen
TCWB (Tinned Copper Wire Braid)

Sheath
LSZH (Low Smoke Zero Halogen)

Sheath Colour
● Black

DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km	NOMINAL THICKNESS OF INSULATION mm	NOMINAL DIAMETER mm	NOMINAL WEIGHT kg/km
SE0875-5C	5	1.16	17.33	0.9	14.3	360
SE0875-10C	10	1.16	17.33	0.9	23.4	740

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.

CABLE THIRD-PARTY ACCREDITATION



London Underground Limited (LUL) certified and listed on the Approved Products Register as meeting the requirements for installation within their network

STANDARDS

SE 0875 LUL 1-085

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/85/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].

