

9842 - 600V LSZH Alternative Cable



Eland Product Group: A3B

APPLICATION

9842 - 600V LSZH Alternative cable is a 24 AWG low capacitance cable with a high level of screening. Provides interference free, high speed data transmission suitable for RS485 applications.

CHARACTERISTICS

Voltage Rating
600V

Temperature Rating
Fixed: -20°C to +80°C

CONSTRUCTION

Conductor
Class 2 stranded tinned copper conductor

Insulation
PE (Polyethylene)

Screen
Al/PET (Aluminium polyester foil)

Drain Wire
Stranded Tinned copper

Braid
TCWB (Tinned Copper Wire Braid)

Sheath
LSZH (Low Smoke Zero Halogen)

Core Identification
Pair 1: ● Blue/White ● White/Blue
Pair 2: ● Orange/White ● White/Orange

Sheath Colour
● Grey

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.





DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B9842NH600V	2	AWG24(7)	0.2	8.65	92

ELECTRICAL CHARACTERISTICS

MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C
ohms/km

86.2