

# Belden 8772 Multi-Conductor Audio, Control and Instrumentation Cable



Eland Product Group: A4B

## APPLICATION

A multi-core cable for audio, control and instrumentation applications.

## CHARACTERISTICS

**Voltage Rating**  
300V

**Temperature Rating**  
-20°C to +60°C

**Minimum Bending Radius**  
10 x overall diameter

## CONSTRUCTION

**Conductor**  
Class 2 stranded tinned copper

**Insulation**  
PE (Polyethylene)

**Screen**  
Beldfoil<sup>®</sup> (Aluminium foil polyester tape)

**Drain Wire**  
Tinned copper

**Sheath**  
PVC (Polyvinyl Chloride)

**Core Identification**  
● Black ● Red ● Transparent

**Sheath Colour**  
● Grey

## STANDARDS

Belden 8772, UL Style 2093

Vertical tray fire propagation and smoke release test:  
UL 1685 FT1

## ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab<sup>®</sup>, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



## REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup> as meeting the requirements of the BSI RoHS Trusted Kitemark<sup>™</sup>.





## DIMENSIONS

ELAND PART NO.	BELDEN REFERENCE	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A4B8772	8772	3	AWG20(7)	0.3	5.53	43.15

## ELECTRICAL CHARACTERISTICS

AWG (NO. OF STRANDS)	CAPACITANCE pF/m		MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
	Conductor to Conductor	Conductor to Shield	
AWG20(7)	88.58	167.33	32.81

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.