

# Belden 9740 Multi-Conductor Audio, Control and Instrumentation Cable



Eland Product Group: A4B

## APPLICATION

General purpose unshielded multi-pair cable for indoor use in audio, control and instrumentation applications.

## CHARACTERISTICS

**Voltage Rating**  
300V

**Temperature Rating**  
-20°C to +80°C

**Minimum Bending Radius**  
10 x overall diameter

## CONSTRUCTION

**Conductor**  
Class 2 stranded tinned copper

**Insulation**  
PVC (Polyvinyl Chloride)

**Sheath**  
PVC (Polyvinyl Chloride)

**Core Identification**  
● Black ● Red

**Sheath Colour**  
● Grey

## STANDARDS

Belden 9740

Vertical tray fire propagation and smoke release test UL 1685 FT4

## THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](https://www.elandcables.com/company/about-us/esg-sustainability)



SCIENCE  
BASED  
TARGETS

**BUSINESS  
AMBITION FOR 1.5°C**



## REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.





## DIMENSIONS

ELAND PART NO.	BELDEN REFERENCE	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A4B9740	9740	1	AWG18(16)	0.823	5.33	32.74

## ELECTRICAL CHARACTERISTICS

AWG (NO. OF STRANDS)	CAPACITANCE - CONDUCTOR TO CONDUCTOR pF/m	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
AWG18(16)	83.66	22.50

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.