



Drincable 800 Cable



Eland Product Group: A6E

APPLICATION

WRAS-approved cable suitable for permanent submersion in potable water up to a depth of 800m. Can be used where improved chemical and abrasion resistance is required, including submersible pumps in mining application, submersible pumps for drinking water, depuration / chlorination systems, swimming pool lighting, aquariums and processing and preserving systems of drink and foodstuff. Water resistance tested to EN 50525-2-21 (AD8 condition).

CHARACTERISTICS

Voltage Rating U_o/U
0.6/1kV

Test Voltage
4kV

Temperature Rating
-25°C to +90°C

Maximum Water Temperature
+80°C

Minimum Bending Radius
Fixed: 3 x overall diameter
Flexed: 5 x overall diameter

CONSTRUCTION

Conductor
Class 5 tinned copper conductor

Insulation
EPR compound

Sheath
Elastomeric cross-linked compound

Core Identification
3 core: ● Blue ● Brown ● Green/Yellow
4 core: ● Brown ● Black ● Grey ● Green/Yellow
5 core: ● Blue ● Brown ● Black ● Grey ● Green/Yellow

Sheath Colour
● Light Blue

STANDARDS

IEC 60811-2-1, EN 50525-2-21, EN 50363-1,
IEC/EN 60228, KTW, DVGW W270, DM174/04



THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/853/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A6E10015	1	1.5	5.55	35
A6E10025	1	2.5	6.2	55
A6E10040	1	4	7	70
A6E10060	1	6	7.8	100
A6E1010	1	10	9.3	155
A6E1016	1	16	10.2	215
A6E1025	1	25	11.7	305
A6E1035	1	35	13.2	380
A6E1050	1	50	15.3	570
A6E1070	1	70	17.6	795
A6E1095	1	95	19.7	1030
A6E1120	1	120	22.2	1305
A6E1150	1	150	24.1	1590
A6E1185	1	185	26.7	1980
A6E1240	1	240	29.8	2560
A6E1300	1	300	32.9	3180
A6E1400	1	400	36.5	4050
A6E1500	1	500	41.7	4990
A6E3G0015	3G	1.5	9.3	110
A6E3G0025	3G	2.5	10.6	180
A6E3G0040	3G	4	11.8	225
A6E3G0060	3G	6	13.1	295
A6E3G010	3G	10	16.9	480
A6E3G016	3G	16	19.2	680
A6E3G025	3G	25	23.7	995
A6E3G035	3G	35	26.6	1325
A6E3G050	3G	50	31.3	1890
A6E3G070	3G	70	35.9	2620
A6E3G095	3G	95	40.2	3225
A6E3G120	3G	120	45.7	4130
A6E3G150	3G	150	50.6	5115
A6E3G185	3G	185	55.1	6200
A6E3G240	3G	240	62	7850
A6E3G300	3G	300	69	10050
A6E4G0015	4G	1.5	10.2	135
A6E4G0025	4G	2.5	11.8	200
A6E4G0040	4G	4	13.2	270
A6E4G0060	4G	6	14.6	380
A6E4G010	4G	10	18.8	630
A6E4G016	4G	16	21.1	870
A6E4G025	4G	25	26.3	1310
A6E4G035	4G	35	29.4	1725
A6E4G050	4G	50	34.7	2490
A6E4G070	4G	70	39.8	3420
A6E4G095	4G	95	45.4	4480
A6E4G120	4G	120	50.6	5605
A6E4G150	4G	150	56.1	6985
A6E4G185	4G	185	61.6	8465
A6E4G240	4G	240	68.9	10900



CONDUCTORS

NOMINAL CROSS SECTIONAL AREA mm ²	ELECTRICAL RESISTANCE AT 20°C ohms/km	PHASE REACTANCE AT 50HZ ohms/km	
	Flexible Conductors Tinned Copper	Single Core Cables	Multi-core Cables
1.5	13.7	0.168	0.118
2.5	8.21	0.155	0.109
4	5.09	0.143	0.101
6	3.39	0.135	0.0955
10	1.95	0.119	0.0861
16	1.24	0.112	0.0817
25	0.795	0.106	0.0813
35	0.565	0.101	0.0783
50	0.393	0.101	0.0779
70	0.277	0.0965	0.0751
95	0.210	0.0975	0.0762
120	0.164	0.0939	0.0740
150	0.132	0.0928	0.0745
185	0.108	0.0908	0.0742
240	0.0817	0.0902	0.0752
300	0.0654	0.0895	0.0750
400	0.0495	0.0876	0.0742
500	0.0391	0.0867	0.0744

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY A	
	Laying in Air	Laying in Water
1.5	23	29
2.5	32	38
4	42	52
6	54	67
10	75	94
16	100	125
25	127	166
35	158	205
50	192	256
70	246	316
95	298	377
120	346	438
150	399	505
185	456	577
240	538	681
300	621	785

Conductor temperature: +90°C
 Ambient air/water temperature: +30°C

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.