

9843 - LSZH 300V Alternative Cable



Eland Product Group: A3B

APPLICATION

9843 Alternative cable is a 24 AWG low capacitance cable with a high level of screening. Provides interference free, high speed data transmission suitable for RS485 applications.

CHARACTERISTICS

Voltage Rating

300V

Temperature Rating

Fixed: -20°C to +80°C

Minimum Bending Radius

10 x overall diameter

CONSTRUCTION

Conductor

Class 2 stranded tinned copper conductor

Insulation

PE (Polyethylene)

Inner Sheath

LSZH (Low Smoke Zero Halogen) compound

Screen 1

Al/PET (Aluminium foil/Polyester tape)

Screen 2

TCWB (Tinned Copper Wire Braid)

Drain Wire

Stranded Tinned copper

Sheath

LSZH (Low Smoke Zero Halogen)

Core Identification

Pair 1: Blue/White White/Blue

Pair 2: Orange/White White/Orange

Pair 3: White/Green Green/White

Sheath Colour

Grey

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



FS 672069



EMS 672067

OHS 672066

REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



KM 634267





DIMENSIONS

ELAND PART NO.	NO. OF PAIRS	AWG NO. OF STRANDS	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A3B9843LSZH	3	AWG24(7)	0.2	9.15	108

ELECTRICAL CHARACTERISTICS

VELOCITY TO PROPAGATION %	IMPEDANCE ohms	CAPACITANCE AT 1kHz pF/m	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km
66	120	90	90.41

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.