

# Copper Tube Pin Terminals



Eland Product Group: **FCA**

## APPLICATION

This range of pin terminals is designed to terminate conductors into contact blocks. The internal diameters suit standard cables as defined in BS EN 60228.



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

## DIMENSIONS

ELAND PART NO.	CABLE SIZE mm <sup>2</sup>	TOTAL LENGTH mm	PIN LENGTH mm	ENTRY WIDTH mm	PIN WIDTH mm	TOTAL WIDTH mm	PACK QUANTITY
FTP15	1.5	12.5	8	1.8	1.7	3.8	100
FTP25	2.5	12.5	8	2.4	1.7	4.4	100
FTP6	6	15.8	10	3.6	3.6	5.6	100
FTP10	10	24.1	13.2	4.8	4.3	6.8	100
FTP16	16	34.3	18.2	6	5.3	8	100
FTP25	25	38	18.5	7	7	9	100
FTP35	35	43.4	18.8	8.2	7	10.2	100
FTP50	50	50.5	19.2	9.5	8.4	12	100
FTP70	70	55	23	11.2	11	14.2	50
FTP95	95	55	23	13.4	12.5	16.4	50