

Conduit Contractor Packs



Eland Product Group: **FCA**

APPLICATION

For enclosing electrical cables and wires particularly where a flexible approach is required due to installation restrictions. Comes with 10 x terminations. Non flame propagating.

CHARACTERISTICS

Temperature

Fixed: -5°C
Flexed: +60°C

Pack Contents

This is a flexible conduit in either 20mm or 25mm aperture with 10 plastic terminations with each pack

CONSTRUCTION

Material

PVC (Polyvinyl Chloride)

STANDARDS

UL94V2

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DESCRIPTION

ELAND PART NO.	OUTER DIAMETER mm
M20 CONN-PACK	20
M25 CONN-PACK	25