

Cable Ties - Nylon



Eland Product Group: **FCA**

CONSTRUCTION

Material

Natural and black nylon 6/6

STANDARDS

UL94V2



CHARACTERISTICS

Temperature

-40°C to +85°C

The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

DIMENSIONS

Tie Width 2.5mm

ELAND PART NO.		LENGTH mm	WIDTH mm	MAXIMUM BUNDLE DIAMETER mm	MINIMUM TENSILE STRENGTH	PACK QUANTITY
NATURAL	BLACK					
FTR100-25	FTR100-25B	100	2.5	18	8.2	100
FTR160-25	FTR160-25B	160	2.5	40	8.2	100

Tie Width 3.6mm

ELAND PART NO.		LENGTH mm	WIDTH mm	MAXIMUM BUNDLE DIAMETER mm	MINIMUM TENSILE STRENGTH	PACK QUANTITY
NATURAL	BLACK					
FTR100-3.6	FTR100-3.6B	100	3.6	18	8.2	100
FTR160-3.6	FTR160-3.6B	160	3.6	40	8.2	100

Tie Width 4.8mm

ELAND PART NO.		LENGTH mm	WIDTH mm	MAXIMUM BUNDLE DIAMETER mm	MINIMUM TENSILE STRENGTH	PACK QUANTITY
NATURAL	BLACK					
FTR100-4.8	FTR100-4.8B	100	4.8	18	8.2	100
FTR160-4.8	FTR160-4.8B	160	4.8	40	8.2	100

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.