

K-Type Cable Markers and Carrier Strips





Eland Product Group: FCA

APPLICATION

Ideal for marking and identifying large cables, bundles, conduit or pipes. Excellent resistance to seawater, fuels and oils.

CONSTRUCTION

Material

K-Type Cable Markers: PVC (Polyvinyl Chloride)
Carrier Strips for K-Type Markers: Tough PVC (Polyvinyl Chloride)

CHARACTERISTICS

Temperature

Service temperature: -40°C to +70°C

Marking

A-Z, 0-9, +, -, / $^{\circ}$ and earth

DESCRIPTION

Markers slide onto a carrier strip which cable ties onto cable or pipe. Black print on yellow marker UV resistant according to UL94V2

STANDARDS

UL94V2

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability





SCIENCE BASED AMBITION FOR 1.5°C





REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.







DIMENSIONS

K-Type Cable Markers

ELAND PART NO.	FOR CABLE DIAMETER	CABLE SIZE mm ² (BS 6004, BS 6231)	MARKER LENGTH mm	QUANTITY/REEL
FER65	4.2 - 7	4 - 10	6	500

Carrier Strips for K-Type Markers

ELAND PART NO.	NO. OF DIGIT	BAG
F1132	8 Digits	100
F1131	12 Digits	100
F1133	24 Digits	100



The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.