

# Braided Sleeving



Eland Product Group: **FCA**

## APPLICATION

Braided sleeving is an expanding braided cable cover made from woven polyester, and is used for harnessing cables together.

## CHARACTERISTICS

### Material

Heat-stabilised polyester

### Limited Oxygen Index (L.O.I.)

27.5%

### Melting Point

+257°C

### Withstands Peaks

+150°C

## STANDARDS

UL 94 HB



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

## DIMENSIONS

ELAND PART NO.	MINIMUM CABLE DIAMETER	MAXIMUM CABLE DIAMETER	PACK QUANTITY
	mm	mm	
F6TS/6	5	9	100
F6TS/8	6	12	100
F6TS/10	8	14	100
F6TS/12	10	16	50
F6TS/15	12	20	50
F6TS/20	18	25	50
F6TS/25	22	30	25
F6TS/30	26	35	25
F6TS/35	30	40	25
F6TS/40	35	45	25
F6TS/50	45	55	25

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.