

Wraparound Cable Cleat



Eland Product Group: **FCG**

APPLICATION

Designed to fix, retain and support cables. Single fixing provides a simple but strong means of securing cables.



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

CONSTRUCTION

Material

UV resistant polypropylene. Made of non-flame propagating black polypropylene

CHARACTERISTICS


Temperature Rating

Constant: 80°C
Intermittent: 95°C

Colour

● Black

DIMENSIONS



ELAND PART NO.	MAXIMUM DIAMETER OF CABLE		A mm	B mm	BOLT HOLES mm	PACK QUANTITY
	mm	inches				
NYLON CLEAT CC5	12.7	0.5	30	16	6	100
NYLON CLEAT CC6	15.2	0.6	32	17	6	100
NYLON CLEAT CC7	17.8	0.7	35	21	6	100
NYLON CLEAT CC8	20.3	0.8	37	24	6	100
NYLON CLEAT CC9	22.8	0.9	40	26	6	100
NYLON CLEAT CC10	25.4	1	43	29	6	100
NYLON CLEAT CC11	27.7	1.1	48	33	6	100
NYLON CLEAT CC12	30.5	1.2	56	36	10	50
NYLON CLEAT CC14	35.5	1.4	62	41	10	50
NYLON CLEAT CC16	40.6	1.6	67	47	10	50
NYLON CLEAT CC18	45.7	1.8	71	52	10	50
NYLON CLEAT CC20	50.8	2	77	56	10	50

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.