

# Scame IP44 Plug



Eland Product Group: **SCA**

## APPLICATION

IP44 industrial plug for fixed or temporary use where ingress protection is required.

## CONSTRUCTION

### Material

Halogen free engineering plastic

## STANDARDS

BS EN 60309-1, BS EN 60309-2



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

## CHARACTERISTICS

### Voltage Rating

100/480V

### Operating Temperature

-25°C to +40°C

### Maximum Operating Temperature

+60°C

## DIMENSIONS

ELAND PART NO.	POLES	AMPS	TYPE	VOLTAGE RATING V	COLOUR
SP-44SCYW/16A	2P+E	16	Screw	100 - 130	Yellow
SP-44SCYT/16A	2P+E	16	Screw	100 - 130	Yellow/Transparent
SP-44SCBL/16A	2P+E	16	Screw	200 - 250	Blue
SP-44SCBK/16A	2P+E	16	Screw	200 - 250	Black
SP-44SCBT/16A	2P+E	16	Screw	200 - 250	Blue/Transparent
SP-44SCRD/16A	2P+E	16	Screw	380 - 415	Red
SP-44IPYW/16A	2P+E	16	Insulation Perforation	100 - 130	Yellow
SP-44IPYT/16A	2P+E	16	Insulation Perforation	100 - 130	Yellow/Transparent
SP-44IPBL/16A	2P+E	16	Insulation Perforation	200 - 250	Blue
SP-44IPBK/16A	2P+E	16	Insulation Perforation	200 - 250	Black
SP-44IPBT/16A	2P+E	16	Insulation Perforation	200 - 250	Blue/Transparent
SP-44IPRD/16A	2P+E	16	Insulation Perforation	380 - 415	Red
SP-44SCYW/32A	2P+E	32	Screw	100 - 130	Yellow
SP-44SCBL/32A	2P+E	32	Screw	200 - 250	Blue
SP-44SCBK/32A	2P+E	32	Screw	200 - 250	Black
SP-44SCRD/32A	2P+E	32	Screw	380 - 415	Red
SP3-44SCBL/16A	3P+E	16	Screw	200 - 250	Blue
SP3-44SCRD/16A	3P+E	16	Screw	380 - 415	Red
SP3-44SCBK/16A	3P+E	16	Screw	380 - 415	Black
SP3-44IPBL/16A	3P+E	16	Insulation Perforation	200 - 250	Blue
SP3-44IPRD/16A	3P+E	16	Insulation Perforation	380 - 415	Red
SP3-44IPBK/16A	3P+E	16	Insulation Perforation	380 - 415	Black
SP3-44SCBL/32A	3P+E	32	Screw	200 - 250	Blue
SP3-44SCRD/32A	3P+E	32	Screw	380 - 415	Red
SP3-44SCBK/32A	3P+E	32	Screw	380 - 415	Black
SP4-44SCRD/16A	3P+N+E	16	Screw	346 - 415	Red
SP4-44SCBK/16A	3P+N+E	16	Screw	346 - 415	Black
SP4-44IPRD/16A	3P+N+E	16	Insulation Perforation	346 - 415	Red
SP4-44IPBK/16A	3P+N+E	16	Insulation Perforation	346 - 415	Black
SP4-44SCRD/32A	3P+N+E	32	Screw	346 - 415	Red
SP4-44SCBK/32A	3P+N+E	32	Screw	346 - 415	Black