



NPG 19/33 (36)kV Single Core Unarmoured Copper Conductors



APPLICATION

Medium voltage DNO copper power cable approved to Northern Powergrid (NPG) specification and manufactured by G81 suppliers for connections from existing grid to new sub-main developments.

CHARACTERISTICS

Voltage Rating (U₀/U)
19/33 (36)kV

Temperature Rating
0°C to +90°C

CONSTRUCTION

Conductor

Class 2 Stranded Copper Conductor

Conductor Screen

Fully bonded semi-conductive compound

Insulation

XLPE (Cross-Linked Polyethylene)

Insulation Screen

Semi-conductive compound

Screen

Copper Wires and Equalising Tape

Separator

Binding tape

Sheath

MDPE (Medium-Density Polyethylene)

Sheath Colour

● Black

STANDARDS

BS 7870-4.10, ES 02-0940



THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL AREA OF METALLIC SCREEN mm ²	NOMINAL OVERALL DIAMETER (OR TRIPLEX GROUP IF APPLICABLE) mm ²	NOMINAL WEIGHT (OR TRIPLEX GROUP IF APPLICABLE) kg/km	MINIMUM BENDING RADIUS mm	MAXIMUM PULLING TENSION N
D310120BK000	1	500	35	54	6200	1070	24510
D310121BK000	1	630	35	58	7600	1100	30890
D310130BK000	1	800	35	66	9400	1210	39228

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km	MAXIMUM AC RESISTANCE OF CONDUCTOR AT 90°C ohms/km	REACTANCE AT 50HZ ohms/km	CAPACITANCE µf/km	1 SECOND SHORT CIRCUIT RATING OF CONDUCTOR kA	1 SECOND SHORT CIRCUIT RATING OF METALLIC SCREEN kA
500	0.0366	0.0510	0.105	0.29	72.1	5
630	0.0283	0.042	0.103	0.32	90.7	5
800	0.0221	0.0350	0.098	0.35	115.1	5

CURRENT CARRYING CAPACITY

NOMINAL CROSS SECTIONAL AREA mm ²	DIRECT BURIED Amps	IN DUCTS Amps	IN AIR Amps
500	760	700	1020
630	850	780	1160
800	930	860	1290

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.