


ELAND[®] CABLES

FLR4Y-A Cable



Eland Product Group: A2A

APPLICATION

The FLR4Y-A cable is a single core polyamide insulated automotive wire, particularly suited for use as fuel gauge wire, this cable is gasoline and diesel resistant.

CHARACTERISTICS

Temperature Rating

-40°C to +105°C

CONSTRUCTION

Conductor Cu-ETP1 Bare Copper

Insulation PA (Polyamide)

Sheath Colour

Blue

STANDARDS

ISO 6722 Class B

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NUMBER			NUMBE OF COR	ES	NOMINAL NOMINAL CROSS- NO. AND SECTION DIAMETER OF WIRES		ND TER RES	MAXIMUM DIAMETER OF CONDUCTOR	MAX		NOMINAL INSULATION THICKNESS	NOMINAL OVERALL DIAMETER	NOMINAL WEIGHT
					mm ² No./		nm mm		mΩ/m		mm	mm	kg/km
A2AT013000035**			1		0.35	7/0.26		0.80	52.00		0.20	1.30	4
A2AT01300005**			1		0.50 19/0.19		19	1.00	37.10		0.22	1.60	6
A2AT01300075**			1		0.75 19/0.23		23	1.20	24.70		0.24	1.90	8
A2AT013000010**			1		1.00	19/0.26		1.35	18.50		0.24	2.10	11
A2AT0130015**			1		1.50	19/0.32		1.70	12.70		0.24	2.40	15
A2AT0130025**			1		2.50	19/0.41		2.20	7.60		0.28	3.00	24
COLOUR	Red	Black	Blue	Yellow	Grey	Brown	White	e Violet	Green	Natura	ıl		
CODE	RD	BK	BL	YW	GR	BR	WH	VI	GN	NT			