



XHIRE Cable



Eland Product Group: MP54

APPLICATION

Portuguese MV Cable for power distribution and power supply stations used in Utility and Industrial applications, for rated voltages from 3.6/6kV to 18/30kV. Suitable for fixed installations, directly buried. Good mechanical protection.

CHARACTERISTICS

Voltage Rating U_0/U (Um)

3.6/6 (7.2)kV,
6/10 (12)kV,
8.7/15 (17.5)kV,
12/20 (24)kV,
18/30 (36)kV

Temperature Rating

Conductor maximum operating temperature: 90°C
Maximum short-circuit temperature: 250°C

Minimum Bending Radius

During installation: 15 x overall diameter
After installation: 10 x overall diameter

CONSTRUCTION

Conductor

Class 2 Copper, circular, stranded

Conductor Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Insulation

XLPE (Cross-Linked Polyethylene)

Insulation Screen

Semi-conductive XLPE (Cross-Linked Polyethylene)

Metallic Screen

Copper tape screen

Filler

Extruded polymeric material

Bedding

PE (polyethylene)

Armour

SWA (Galvanized Steel Wire Armoured)

Sheath

Extruded PE (polyethylene) type ST7

Sheath Colour

● Black

STANDARDS

IEC 60228, IEC 60502-2

ISO/IEC 17025 LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab®, an ISO/IEC 17025 accredited cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



8578



FS 672069



EMS 672067



OHS 672066

REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



RM 634267





DIMENSIONS 3.6/6 (7.2)kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP5406kV03025	3	25	13.0	44.5	3320
MP5406kV03035	3	35	14.0	47.0	3775
MP5406kV03050	3	50	15.0	49.5	4340
MP5406kV03070	3	70	16.5	54.0	5280
MP5406kV03095	3	95	18.5	58.0	6325
MP5406kV03120	3	120	20.0	61.5	7290
MP5406kV03150	3	150	21.0	64.5	8300
MP5406kV03185	3	185	22.5	67.5	9640
MP5406kV03240	3	240	25.5	75.0	11985
MP5406kV03300	3	300	28.5	82.0	14475

ELECTRICAL CHARACTERISTICS 3.6/6 (7.2)kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT, T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE µF/km
		In air	Buried				
3	25	143	148	3.6	0.7270	0.38	0.27
3	35	172	177	5.0	0.5240	0.36	0.30
3	50	205	209	7.5	0.3870	0.34	0.33
3	70	253	255	10.0	0.2680	0.32	0.38
3	95	307	304	13.6	0.1930	0.30	0.43
3	120	352	345	17.2	0.1530	0.29	0.48
3	150	397	388	21.5	0.1240	0.28	0.51
3	185	453	437	26.5	0.0991	0.28	0.54
3	240	529	503	34.3	0.0754	0.27	0.60
3	300	599	563	42.9	0.0601	0.26	0.63

DIMENSIONS 6/10 (12)kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP5410KV03025	3	25	15.0	49.0	3775
MP5410KV03035	3	35	16.0	51.5	4255
MP5410KV03050	3	50	17.0	54.5	4850
MP5410KV03070	3	70	18.5	58.5	5815
MP5410KV03095	3	95	20.5	62.5	6830
MP5410KV03120	3	120	22.0	66.5	7885
MP5410KV03150	3	150	23.0	69.5	8960
MP5410KV03185	3	185	24.5	72.5	10290
MP5410KV03240	3	240	27.0	78.5	12455
MP5410KV03300	3	300	30.0	85.0	14935



ELECTRICAL CHARACTERISTICS 6/10 (12)kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
3	25	143	148	3.6	0.7270	0.40	0.22
3	35	172	177	5.0	0.5240	0.38	0.24
3	50	205	209	7.5	0.3870	0.37	0.27
3	70	253	255	10.0	0.2680	0.34	0.30
3	95	307	304	13.6	0.1930	0.32	0.34
3	120	352	345	17.2	0.1530	0.31	0.37
3	150	397	388	21.5	0.1240	0.30	0.39
3	185	453	437	26.5	0.0991	0.29	0.42
3	240	529	503	34.3	0.0754	0.28	0.48
3	300	599	563	42.9	0.0601	0.27	0.53

DIMENSIONS 8.7/15 (17.5)kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP5415KV03025	3	25	17.0	54.5	4335
MP5415KV03035	3	35	18.0	57.0	4835
MP5415KV03050	3	50	19.0	59.5	5470
MP5415KV03070	3	70	21.0	63.5	6425
MP5415KV03095	3	95	22.5	67.5	7505
MP5415KV03120	3	120	24.5	71.5	8600
MP5415KV03150	3	150	25.5	74.5	9730
MP5415KV03185	3	185	26.5	77.5	10985
MP5415KV03240	3	240	29.5	83.5	13290

ELECTRICAL CHARACTERISTICS 8.7/15 (17.5)kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
3	25	143	148	3.6	0.7270	0.43	0.18
3	35	172	177	5.0	0.5240	0.41	0.20
3	50	205	209	7.5	0.3870	0.39	0.21
3	70	253	255	10.0	0.2680	0.36	0.24
3	95	307	304	13.6	0.1930	0.34	0.27
3	120	352	345	17.2	0.1530	0.33	0.29
3	150	397	388	21.5	0.1240	0.32	0.31
3	185	453	437	26.5	0.0991	0.31	0.33
3	240	529	503	34.3	0.0754	0.30	0.38



DIMENSIONS 12/20 (24)kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP5420KV03035	3	35	20.0	61.5	5325
MP5420KV03050	3	50	21.0	64.5	6000
MP5420KV03070	3	70	23.0	68.5	7045
MP5420KV03095	3	95	24.5	72.5	8190
MP5420KV03120	3	120	26.5	76.5	9280
MP5420KV03150	3	150	27.5	79.0	10330
MP5420KV03185	3	185	28.5	82.0	11760

ELECTRICAL CHARACTERISTICS 12/20 (24)kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
3	35	172	177	5.0	0.5240	0.43	0.17
3	50	205	209	7.5	0.3870	0.41	0.19
3	70	253	255	10.0	0.2680	0.37	0.21
3	95	307	304	13.6	0.1930	0.36	0.23
3	120	352	345	17.2	0.1530	0.34	0.25
3	150	397	388	21.5	0.1240	0.33	0.27
3	185	453	437	26.5	0.0991	0.32	0.28

DIMENSIONS 18/30 (36)kV

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER mm		NOMINAL WEIGHT kg/km
			Over Insulation	Overall	
MP5430KV03050	3	50	26.0	76.0	7595
MP5430KV03070	3	70	28.0	80.5	8730
MP5430KV03095	3	95	29.5	86.0	10845
MP5430KV03120	3	120	31.5	90.0	12105

ELECTRICAL CHARACTERISTICS 18/30 (36)kV

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		CONDUCTOR MAXIMUM SHORT-CIRCUIT CURRENT. T=1S kA	MAXIMUM CONDUCTOR DC RESISTANCE AT 20°C ohm/km	INDUCTANCE mH/km	CAPACITANCE μF/km
		In air	Buried				
3	50	205	209	7.5	0.3870	0.45	0.14
3	70	253	255	10.0	0.2680	0.41	0.16
3	95	307	304	13.6	0.1930	0.39	0.18
3	120	352	345	17.2	0.1530	0.38	0.19

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.