

# AS/NZS 5000.2 Single Core PVC-PVC Cable 450/750V



Eland Product Group: AS1

## APPLICATION

Single core PVC cables available for switchboard and control panel wiring, for fixed wiring within other enclosures, or apparatus where the cable is not accessible without the use of tools.

## CHARACTERISTICS

**Rated Voltage U<sub>0</sub>/U**  
450/750V

**Temperature Rating**  
Maximum operating temperature: 90°C

**Minimum Bending Radius**  
3 x overall diameter

## CONSTRUCTION

**Conductor**  
Plain annealed copper

**Insulation**  
PVC V-90 (Polyvinyl Chloride)

**Outer Sheath**  
PVC 3V90 (Polyvinyl Chloride)

**Core Identification**  
Single core (choice) ● Red ● Black

**Sheath Colour**  
○ White

## DIMENSIONS

ELAND PART NO.	NUMBER OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	CONDUCTOR Strands / OD mm	NOMINAL INSULATION THICKNESS mm	NOMINAL OUTER SHEATH THICKNESS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
AS14010010WH**	1	1.0	1/1.13	0.6	0.9	4.1	30
AS14010015WH**	1	1.5	7/0.50	0.6	0.9	4.4	35
AS14010025WH**	1	2.5	7/0.67	0.7	1	5.1	55
AS14010040WH**	1	4	7/0.85	0.8	1.1	6.0	80
AS14010060WH**	1	6	7/1.04	1.0	1.1	6.6	100
AS1401010WH**	1	10	7/1.35	1.0	1.2	7.8	145
AS1401016WH**	1	16	7/1.70	1.0	1.3	9.1	225

\* Designates the insulation colour. For each Eland Cables part number replace with either RD for Red and BK for Black as listed e.g. AS14010010WHRD = 1 core 1mm<sup>2</sup> Red

## STANDARDS

AS/NZS 5000.2, AS 1125, AS 3808

## THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](https://www.elandcables.com/company/about-us/esg-sustainability)



## REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.





## ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTION AREA mm	CURRENT RATINGS			MAXIMUM DC RESISTANCE AT 20 °C Ohm/km	MAXIMUM AC RESISTANCE AT 75 °C Ohm/km	REACTANCE Ohm/km	SINGLE PHASE VOLTAGE DROP mV/A
	In conduit In Air A	Surrounded by thermal insulation A	Buried In Ducts A				
1.0	15	26	20	18.1	27.0	0.168	54.0
1.5	18	34	26	13.6	17.3	0.157	34.6
2.5	26	47	36	7.41	9.45	0.143	18.9
4	35	62	46	4.61	5.88	0.137	11.8
6	46	78	58	3.08	3.93	0.128	7.86
10	62	103	78	1.83	2.33	0.118	4.68
16	82	132	100	1.15	1.47	0.111	2.94