

H03S-K Cable



Eland Product Group: B3I

APPLICATION

Single core non-sheathed electric cables with silicone insulation. These cables are suitable for electric connexion for fixed installations in places with high temperatures, such as ovens or electric cookers.

CHARACTERISTICS

Voltage Rating U_o/U
300V/300V

Test Voltage
2kV

Temperature Rating
Operating: -60°C to +180°C
Maximum Short Circuit Temperature: 350°C (Max. 5 seconds)

Minimum Bending Radius
5 x overall diameter

CONSTRUCTION

Conductor
Class 5 Flexible Bare or Tinned Copper

Insulation
Silicone Rubber

Colour
 ● Black ● Blue ● Brown ● Grey ● Orange ● Pink ● Red
 ● Turquoise ● Violet ○ White ● Green ● Yellow or
 ● Green/Yellow

DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL THICKNESS OF INSULATION mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
B3I0100005**	1	0.5	0.6	2.1	8.3
B3I0100075**	1	0.75	0.6	2.4	11.5
B3I010010**	1	1	0.6	2.5	13.8
B3I010015**	1	1.5	0.7	3.0	19.3
B3I010025**	1	2.5	0.8	3.6	30.8

STANDARDS

EN 50525-2-41, EN 60228, EN 50363-1, IEC/EN 60724,

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/863/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	RESISTANCE AT 20°C Ohms/km	
	Rb	Sn
0.5	39.0	40.1
0.75	26.0	26.7
1	19.5	20
1.5	13.3	13.7
2.5	7.98	8.21

COLOUR IDENTIFICATION

BK	BL	BR	GR	OR	PK	TQ	VI	WH	GN	GY
Black	Blue	Brown	Grey	Orange	Pink	Turquoise	Violet	White	Green	Green/Yellow

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.